



INFORM R4 C DOWN-UP 92748

26826 9220 W-B

AVAILABLE IN



BLACK-BLACK 26826 9220 B-B

BLACK-FLEMISH GOLD 26826 9220 B-FG

FLEMISH GOLD-BLACK 26826 9220 FG-B

WHITE-BLACK 26826 9220 W-B

WHITE-WHITE 26826 9220 W-W



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Suspended
INGRESS PROTECTION	IP20
WEIGHT (KG)	2.2
ADJUSTABILITY	non adjustable
INFORMATION	96 x REFLECTOR WFL-71° (DOWN) EXCL.2 x LED POWER SUPPLY 700mA-DC (DOWN/UP) INCL.3 x CABLE SUSPENSION SINGLE AUTO. 1,6m INCL.1 x CABLE 5 x 0.75mm ²

Electrical info

CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	C
CERTIFICATES	CB, ENEC

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	DOWN: LED cluster 22,9W / CRI>90 (R9: 50) / 2700K / 3456lm UP: LED cluster 11,5W / CRI>90 (R9: 50) / 2700K / 1728lm
SDCM	SDCM3
LM80	L80 > 60000
BEAMANGLE	71°
LED TECHNICS (LIGHT SOURCE)	DOWN: 3456lm // 22,9W // 151lm/W UP: 1728lm // 11,5W // 151lm/W
LED TECHNICS (LUMINAIRE)	DOWN: 2761lm // 26,3W // 105lm/W UP: 1106lm // 13,2W // 84lm/W

Requirements

LED POWER SUPPLY 700mA-DC DIM (Remote)

INFORM R POWERBOX D/U DIM5

Options

CABLE BASE R / S

COVERSET R 62-90-100 / S 62-80-90

CONNECTION ST / CONNECTION TRIMLESS

SUSPENSION ST / SUSPENSION TRIMLESS

For detailed installation instructions, please consult the manual : [26826_XXX0_HAND.pdf](#)


FINISH YOUR SPECIFICATION

Current supply

	203 99 55 ANO CABLE BASE R ANO	☐
	203 99 55 B CABLE BASE R B	☐
	203 99 55 W CABLE BASE R W	☐
	203 99 56 ANO CABLE BASE S ANO	☐
	203 99 56 B CABLE BASE S B	☐
	203 99 56 W CABLE BASE S W	☐

Power box

of Fixtures


 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the ' ' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.		Min current Max current
	26810 0025 B INFORM R POWERBOX D/U DIM5 B	1 ☐
Dimtype: DALI		
	26810 0025 W INFORM R POWERBOX D/U DIM5 W	1 ☐

LED power supplies		# of Fixtures
# of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the ' ' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.		Min current Max current
67 21 103 67 21 103	300 90 64 LED POWER SUPPLY MULTI-POWER DIM7 Dimtype: 1-10V or push button Cutout dimension (mm): 72	1 down 1 up
103 67 21 103 67 21	300 90 68 LED POWER SUPPLY MULTI-POWER DIM5 Dimtype: DALI Cutout dimension (mm): 72	1 down 1 up
Coversets		
Ø10 2 Ø62 2	204 00 62 ANO COVERSET R 62 ANO	
	204 00 62 B COVERSET R 62 B	
	204 00 62 W COVERSET R 62 W	
Ø10 2 Ø90 2	204 00 90 ANO COVERSET R 90 ANO	
	204 00 90 B COVERSET R 90 B	
	204 00 90 W COVERSET R 90 W	
Ø10 2 Ø100 2	204 00 100 ANO COVERSET R 100 ANO	
	204 00 100 B COVERSET R 100 B	
	204 00 100 W COVERSET R 100 W	

DELTALIGHT

INFORM R4 C DOWN-UP 92748

26826 9220 W-B




204 62 62 ANO COVERSET S 62 ANO

☐

204 62 62 B COVERSET S 62 B

☐

204 62 62 W COVERSET S 62 W

☐


204 80 80 ANO COVERSET S 80 ANO

☐

204 80 80 B COVERSET S 80 B

☐

204 80 80 W COVERSET S 80 W

☐

204 90 90 ANO COVERSET S 90 ANO

☐


204 90 90 B COVERSET S 90 B

☐

204 90 90 W COVERSET S 90 W

☐


Suspension parts



328 10 01 SUSPENSION TRIMLESS O.F.A.

☐

Cutout dimension (mm): 62 (CONCRETE: 102)



15225 0340 B SUSPENSION ST B


☐

Cutout dimension (mm): 27

15225 0340 W SUSPENSION ST W

☐

Electric connection parts

	328 10 03 CONNECTION TRIMLESS O.F.A.	☐
Cutout dimension (mm): 62 (CONCRETE: 102)		
	15225 0360 B CONNECTION ST B	☐
Cutout dimension (mm): 43		
	15225 0360 W CONNECTION ST W	☐

Notes: