





SUPER-OH! XS 25 DIM8

308 21 02 83 ED8 W

AVAILABLE IN

BLACK 308 21 02 83 ED8 B

WHITE 308 21 02 83 ED8 W



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Surface mounted, Wall Surface mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.6
ADJUSTABILITY	non adjustable
INFORMATION	INCL.PC SBL

Electrical info

ELECTRICAL	220-240V / 50-60Hz
CLASS	II
POWER SUPPLY	YES
DIM TYPE	mains (phase cut-off)
ENERGY CLASS	F

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 13,5W / CRI>80 / 3000K / 1470lm
LED TECHNICS (LIGHT SOURCE)	1470lm // 13,5W // 109lm/W
LED TECHNICS (LUMINAIRE)	691lm // 15,5W // 45lm/W

For detailed installation instructions, please consult the manual : [308 21 02 XX ED8 HAND.pdf](#)

FINISH YOUR SPECIFICATION

Miscellaneous control equipment

of Fixtures





of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current

DELTALIGHT

SUPER-OH! XS 25 DIM8

308 21 02 83 ED8 W

	300 90 004 ED8 WIRELESS CONTROL DIM8	☐
	Dimtype: WDL = wireless dimmable	
	Cutout dimension (mm): 40	
	300 90 126 FALLING EDGE DIMMER 200W DIM2	16 ☐
	Dimtype: DALI or push button	
	Cutout dimension (mm): 67	

Notes: