



## FRAX MB POLE SUPERSPOT 92708 HONEYCOMB

26026 9210 N

AVAILABLE IN  
ANTHRACITE 26026 9210 N



[View on website](#)



### General info

<b>LOCATION</b>	outdoor
<b>INSTALLATION</b>	Pole Pole top
<b>INGRESS PROTECTION</b>	IP65
<b>PROTECTION AGAINST MECHANICAL IMPACT</b>	IK08
<b>WEIGHT (KG)</b>	2.3
<b>ADJUSTABILITY</b>	0° to 120° swiveling, 360° rotatable
<b>INFORMATION</b>	7 x LENS SP-8° INCL.LED POWER SUPPLY 900mA-DC INCL.HONEYCOMB INCL.1 x CABLE H05 RN-F 3 x 1mm <sup>2</sup> 6m

### Electrical info

<b>ELECTRICAL</b>	220-240V / 50-60Hz
<b>CLASS</b>	I
<b>POWER SUPPLY</b>	YES
<b>DIM TYPE</b>	non-dimmable
<b>ENERGY CLASS</b>	F
<b>CERTIFICATES</b>	CB, ENEC, EPD, RCM

### Lightsource info

<b>LIGHTSOURCE NAME</b>	LED
<b>LIGHTSOURCE</b>	LED cluster 18,2W / CRI>90 (R9: 55) / 2700K / 1884lm
<b>TM-30 VALUES</b>	Rf: 91 / Rg: 100
<b>SDCM</b>	SDCM3
<b>RISKGROUP</b>	RG2
<b>LM80</b>	L80 > 150000
<b>BEAMANGLE</b>	8°
<b>LED TECHNICS (LIGHT SOURCE)</b>	1884lm // 18,2W // 103lm/W
<b>LED TECHNICS (LUMINAIRE)</b>	1432lm // 20,9W // 68lm/W

### Requirements

FRAX BRACKET

### Options

FRAX ANTI VANDAL SCREWS

### Accessories

FRAX M KAP

# DELTALIGHT

## FRAX MB POLE SUPERSPOT 92708 HONEYCOMB

26026 9210 N

For detailed installation instructions, please consult the manual : [26026\\_XXX0\\_HAND.pdf](#)

### FINISH YOUR SPECIFICATION

#### Light altering devices


---




**26070 0020 N** FRAX M KAP N

#### Other


---



**26070 0030** FRAX ANTI VANDAL SCREWS 5 PCS



**26071 0050 N** FRAX POLE 60 BRACKET N



**26071 0060 N** FRAX POLE 80 BRACKET N

Notes: