



INFORM R1 DOWN-UP 92748

26812 9220 B-FG

AVAILABLE IN



BLACK-BLACK 26812 9220 B-B

BLACK-FLEMISH GOLD 26812 9220 B-FG

FLEMISH GOLD-BLACK 26812 9220 FG-B

WHITE-BLACK 26812 9220 W-B

WHITE-WHITE 26812 9220 W-W



[View on website](#)



General info	
LOCATION	indoor
INSTALLATION	Ceiling Suspended
INGRESS PROTECTION	IP20
WEIGHT (KG)	2.2
ADJUSTABILITY	non adjustable
INFORMATION	96 x REFLECTOR WFL-71° (DOWN) EXCL. LED 2 x POWER SUPPLY 700mA-DC (DOWN/UP) INCL. 4 x CABLE SUSPENSION SINGLE AUTO. 1,6m INCL. 1 x CABLE 5 x 0.75mm ²

Electrical info	
CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	C
CERTIFICATES	CB, ENEC

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	DOWN: LED cluster 22,9W / CRI>90 (R9: 50) / 2700K / 3456lm UP: LED cluster 11,5W / CRI>90 (R9: 50) / 2700K / 1728lm
SDCM	SDCM3
LM80	L80 > 60000
BEAMANGLE	71°
LED TECHNICS (LIGHT SOURCE)	DOWN: 3456lm // 22,9W // 151lm/W UP: 1728lm // 11,5W // 151lm/W
LED TECHNICS (LUMINAIRE)	DOWN: 2761lm // 26,3W // 105lm/W UP: 1106lm // 13,2W // 84lm/W


Requirements	
LED POWER SUPPLY 700mA-DC DIM (Remote)	

Options	
CABLE BASE R / S	
COVERSET R 62-90-100 / S 62-80-90	
CONNECTION ST / CONNECTION TRIMLESS	
SUSPENSION ST / SUSPENSION TRIMLESS	

For detailed installation instructions, please consult the manual : [26812_XXX0_HAND.pdf](#)



FINISH YOUR SPECIFICATION

Current supply

	☐ 203 99 55 ANO CABLE BASE R ANO
	☐ 203 99 55 B CABLE BASE R B
	☐ 203 99 55 W CABLE BASE R W
	☐ 203 99 56 ANO CABLE BASE S ANO
	☐ 203 99 56 B CABLE BASE S B
	☐ 203 99 56 W CABLE BASE S W

LED power supplies

of Fixtures






 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the ' ' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.		Min current Max current
	300 90 64 LED POWER SUPPLY MULTI-POWER DIM7 Dimtype: 1-10V or push button Cutout dimension (mm): 72	1 down 1 up ☐
	300 90 68 LED POWER SUPPLY MULTI-POWER DIM5 Dimtype: DALI Cutout dimension (mm): 72	1 down 1 up ☐

DELTALIGHT

INFORM R1 DOWN-UP 92748



26812 9220 B-FG

Coversets


	<u>204 00 62 ANO</u>	COVERSET R 62 ANO	☐
	<u>204 00 62 B</u>	COVERSET R 62 B	☐
	<u>204 00 62 W</u>	COVERSET R 62 W	☐
	<u>204 00 90 ANO</u>	COVERSET R 90 ANO	☐
	<u>204 00 90 B</u>	COVERSET R 90 B	☐
	<u>204 00 90 W</u>	COVERSET R 90 W	☐
	<u>204 00 100 ANO</u>	COVERSET R 100 ANO	☐
	<u>204 00 100 B</u>	COVERSET R 100 B	☐
	<u>204 00 100 W</u>	COVERSET R 100 W	☐
	<u>204 62 62 ANO</u>	COVERSET S 62 ANO	☐
	<u>204 62 62 B</u>	COVERSET S 62 B	☐
	<u>204 62 62 W</u>	COVERSET S 62 W	☐
	<u>204 80 80 ANO</u>	COVERSET S 80 ANO	☐
	<u>204 80 80 B</u>	COVERSET S 80 B	☐

INFORM R1 DOWN-UP 92748


26812 9220 B-FG

	204 80 80 W COVERSET S 80 W	☐
	204 90 90 ANO COVERSET S 90 ANO	☐
	204 90 90 B COVERSET S 90 B	☐
	204 90 90 W COVERSET S 90 W	☐

Suspension parts

	328 10 01 SUSPENSION TRIMLESS O.F.A.	☐
	Cutout dimension (mm): 62 (CONCRETE: 102)	
	15225 0340 B SUSPENSION ST B	☐
	Cutout dimension (mm): 27	
	15225 0340 W SUSPENSION ST W	☐

Electric connection parts

	328 10 03 CONNECTION TRIMLESS O.F.A.	☐
	Cutout dimension (mm): 62 (CONCRETE: 102)	
	15225 0360 B CONNECTION ST B	☐
	Cutout dimension (mm): 43	
	15225 0360 W CONNECTION ST W	☐

DELTALIGHT

INFORM R1 DOWN-UP 92748

26812 9220 B-FG

Notes: