# M-MICROSPY 39 C



Despite its minimalistic appearence, the Spy pendant wows you with their powerful and striking light effect. As a pendant module its slenderness allows you to create playful or humble set-ups by grouping multiple luminaires or choosing just one single pendant.

| Specification  |                                  |
|----------------|----------------------------------|
| LED Aperture:  | 1 <sup>5</sup> / <sub>16</sub> " |
| Adjustability: | Fixed                            |
| Rating:        | IP20                             |

| Performance      |             |
|------------------|-------------|
| LED Maintenance: | L90>50,000h |
| McAdam Step:     | 2           |
| CRI:             | 90          |
| *MP:             | 7W          |

| Delivered Lumens | 2700K | 3000K | 3500K |
|------------------|-------|-------|-------|
| M-Microspy 39 C: | 507lm | 530lm | 549lm |

Listing ETL certified to US and Canadian safety standards. Warranty 5-year limited warranty.

Ordering ALL BOXES MUST BE FILLED IN TO CORRECTLY ORDER

Example: SPY3904PC-SPWS27-B-M-MDL

| Luminaire  | Size                                  | Length                                  | Style                                | Power*                      | Optic                       | ССТ                | - Finish          | Application <sup>(1)</sup>                                  | - Controls                                       |
|------------|---------------------------------------|---|--------------------------------------|-----------------------------|-----------------------------|--------------------|-------------------|---|--|
| SPY<br>SPY | <b>39</b><br>38mm / 1¹/₂"<br>Diameter | <b>04</b><br>400mm / 15³/₄"<br>Diameter | PC<br>Pendant, 5' cable<br>suspended | <b>SP</b><br>Standard Power | <b>WS</b><br>Medium<br>Wide | <b>27</b><br>2700K | <b>B</b><br>Black | M<br>Shiftline M26H /<br>Shiftline M26H +                   | MDL <sup>(2)</sup><br>0-10V dim via<br>Modulator |
|            |                                       |   |                                      |                             | Spot 45°                    | <b>30</b><br>3000K | <b>W</b><br>White | SBL <sup>(2)</sup> /<br>Shiftline M26L /<br>Splitline M20 / | <b>D5</b><br>Dali dim                            |
|            |                                       |   |                                      |                             |                             | <b>35</b><br>3500K |                   | Splitline M20 ST /<br>Splitline M52 Profile                 | <b>WD</b> <sup>(2)</sup><br>Wireless dim         |

1 Profile system ahrdware specified separately. 2 Shiftline M26H + SBL only available with Controls D5.

# **Related Products**

M-Spy 27/39, M-Spy 52/66/Focus, M-Gibbo, M-Tweeter BL, Spy 27, Microspy In, Gibbo






# **Finish Options**

### M-MICROSPY 39 C



## **Photometric Data**

#### M-MICROSPY 39 C



# Installation Options

Delta Light's Magnetic Systems all utilize 48V remote power supplies. With a maximum of 96W per power supply, the below details maximum magnetic modules per power feed.

| Maximum Capacity per<br>Remote Power Supply | M-Microspy 39 C |
|---|-----------------|
| *SP:  | 12              |

FOR SYSTEM HARDWARE, REFER TO THE FOLLOWING PROFILE SYSTEMS: Shiftline M26H (surface/suspended, high-height, optional curved corner connectors) Shiftline M26H + SBL (surface/suspended, high-height, integral continuous light line) Shiftline M26L (surface/suspended, low-height, stacking possible) Splittine M20 (recessed, knife-edge, optional curved corner connectors) Splittine M20 (recessed, knife-edge, optional curved corner connectors) Splittine M20 ST (recessed, knife-edge)

As technology changes, please use information above as guidance. For most recent updated information please contact factory. Specifications subject to change without notice.

