M-MICROSPY C



Despite its minimalistic appearence, the Spy pendant wows you with its powerful and striking light effect. As a pendant module its slenderness allows you to create playful or humble set-ups by grouping multiple luminaires or choosing just one single pendant.

Specification	
LED Aperture:	1 5/16"
Adjustability:	Fixed
Rating:	Damp

Performance	
CRI / TM-30 (3000K):	90 / Rf: 90 / Rg: 99
SDCM:	1
LED Maintenance:	L90B10>50,000h
*Standard Power:	6.7W

Delivered Lumens	2700K	3000K	3500K
M-Microspy 39 C:	507	530	549

Listing
ETL certified to US and Canadian safety standards.

Warranty
5-year limited warranty.

Ordering
ALL BOXES MUST BE FILLED IN TO CORRECTLY ORDER

Example: SPY3904-27WSSP-B-M-MDL

Luminaire	Size	Length	CCT	Optic**	Power*	Finish	Style	Application[1]	Controls
SPY MICROSPY C	**39** 38mm / 1 1/2" Diameter	**04** 400mm / 15 3/4" Diameter	**27** 2700K **30** 3000K **35** 3500K	**WS** Medium Wide Spot 45°	**SP** Standard Power	**B** Black **W** White	**PC** Pendant, 5' cable suspended	**M** Shiftline M26H / Shiftline M26H + SBL[2] / Shiftline M26L / Splitline M20 / Splitline M20 ST / Splitline M52 Profile	**MDL**[2] 0-10V dim via Modulator **D5** Dali dim **WD**[2] Wireless dim


1 Low voltage system hardware specified separately.
2 Shiftline M26H + SBL only available with Controls D5.

Related Products

M-Spy 27/39, M-Spy 52/66/Focus, M-Microspy C, M-Cuppa, M-Gibbo, M-Tweeter BL, Spy 27, Microspy In, Spy C, Gibbo

Finish Options

M-MICROSPY 39 C





BLACK


WHITE

Photometric Data

M-MICROSPY 39 C



WS 45*

Installation Options

Delta Light's Magnetic Systems all utilize 48V remote power supplies. With a maximum of 96W per power supply, the below details maximum magnetic modules per power feed.

Maximum Capacity per Remote Power Supply	M-Microspy 39 C
*Standard Power:	12

FOR SYSTEM HARDWARE, REFER TO THE FOLLOWING PROFILE SYSTEMS:
Shiftline M26H (surface/suspended, high-height, optional curved corner connectors)
Shiftline M26H + SBL (surface/suspended, high-height, integral continuous light line)
Shiftline M26L (surface/suspended, low-height, stacking possible)
Splitline M20 (recessed, knife-edge, optional curved corner connectors)
Splitline M20 ST (recessed, small trim)
Splitline M52 (recessed, knife-edge)

As technology changes, please use information above as guidance. For most recent updated information please contact factory. Specifications subject to change without notice.