
DELTALIGHT




SL19 - SPY 27 93030 MDL

REFERENCE 27022 9320 B

AVAILABLE IN
BLACK 27022 9320 B
FLEMISH BRONZE 27022 9320 FBR
FLEMISH GOLD 27022 9320 FG
GOLD COLOURED 27022 9320 GC
WHITE 27022 9320 W





View on website

General info	
LOCATION	indoor
INSTALLATION	Low voltage systems Low voltage system mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.2
ADJUSTABILITY	0° to 85° swiveling, 355° rotatable
INFORMATION	REFLECTOR FL-30° EXCL.LED POWER SUPPLY 48V-DC SPY 27 TUBE included (B for all versions W for FW version)

Electrical info	
ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	MDL = 1-10V or DALI or push button
ENERGY CLASS	D
CERTIFICATES	CB, ENEC

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 5,8W / CRI>90 (R9: 52) / 3000K / 787lm
TM-30 VALUES	Rf: 90 / Rg: 99
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	30°
LED TECHNICS (LIGHT SOURCE)	787lm // 5,8W // 135lm/W
LED TECHNICS (LUMINAIRE)	480lm // 6,7W // 72lm/W

Requirements

LED POWER SUPPLY 48V-DC

Options

DIMMABLE MODULATOR

Accessories

VISOR 27

DELTALIGHT

SL19 - SPY 27 93030 MDL

27022 9320 B

For detailed installation instructions, please consult the manual : **27022_XXX0_HAND.pdf**


FINISH YOUR SPECIFICATION

SMART 48

# of Fixtures


Min current | Max current

ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.



300 90 011 SMART 48 MODULATOR DIM9 — 28

Dimtype: 1-10V or DALI or push button



300 90 012 SMART 48 MODULATOR WD — 28


Dimtype: WDL = wireless dimmable

LED power supplies

# of Fixtures


Min current | Max current

ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.




300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN — 15

Dimtype: non-dimmable



300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN — 36

Dimtype: non-dimmable



21012 0230 LED POWER SUPPLY 48V-DC / 100W — 15


Dimtype: non-dimmable

Cutout dimension (mm): 40

DELTALIGHT

SL19 - SPY 27 93030 MDL

27022 9320 B



21012 0240 LED POWER SUPPLY 48V-DC / 200W 30

Dimtype: non-dimmable

Cutout dimension (mm): 40


Light altering devices




24144 0040 B VISOR 27 B

COMPATIBLE COMPOSABLES

SHIFTLINE 19 profile — Available Colours



27011 0050 SL19 - PROFILE 2m



27011 0060 SL19 - PROFILE 3m

Notes: