



OML50 - PRISMATIC LENS DU HO 2296mm 940 DIM5

31637 9405 B

BESCHIKBAAR IN
ZWART 31637 9405 B



[Bekijk op website](#)



Algemene info

LOCATIE	binnen
STOF EN WATERDICHTHEID	IP20
GEWICHT (KG)	3.1
INFO	INCL.DIMMABLE LED POWER SUPPLY (DALI-2 standard) CABLING 1 CIRCUIT

Elektrische info

ELEKTRISCH	220-240V / 0 50-60Hz
KLASSE	I
VOEDING INBEGREPEN	YES
DIM TYPE	DALI
ENERGIE KLASSE	D
CERTIFICATES	EPD, RCM

Info lichtbron

LIGHTSOURCE NAME	LED
LICHTBRON	DOWN: LED cluster 54,3W / CRI>90 (R9: 50) / 4000K / 8487lm UP: LED cluster 42,3W / CRI>90 (R9: 50) / 4000K / 6373lm
TM-30 WAARDEN	Rf: 90 / Rg: 101
SMD	SDCM3
RISK-GROEP	RG1
LM80	L80 > 60000
LED TECHNIEK (LICHTBRON)	DOWN: 8487lm // 54,3W // 160lm/W UP: 6373lm // 42,3W // 151lm/W

Opties

WIRELESS CONTROL DIM5

Notes: