




TGL-TR - SPY 27 92730

18717 9220 W

AVAILABLE IN
SCHWARZ 18717 9220 B
FLEMISH BRONZE 18717 9220 FBR
FLEMISH GOLD 18717 9220 FG
GOLDFARBEN 18717 9220 GC
WEISS 18717 9220 W



 [View on website](#)



General info	
LOCATION	innenbereich
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.1
ADJUSTABILITY	0° to 85° schwenkbar, 355° drehbar
INFORMATION	REFLECTOR FL-30° EXCLLED POWER SUPPLY 350mA-DC SPY 27 TUBE included (B for all versions W for FW version)

Electrical info	
CLASS	III
DIM TYPE	Abhängig von der Art der externen Stromversorgung
ENERGY CLASS	D
CERTIFICATES	CB, ENEC

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 5,8W / CRI>90 (R9: 60) / 2700K / 753lm
TM-30 VALUES	rf: 89 / Rg: 100
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	30°
LED TECHNICS (LIGHT SOURCE)	753lm // 5,8W // 129lm/W

Requirements	
LED POWER SUPPLY 350mA-DC DIM	

Accessories	
VISOR 27	

For detailed installation instructions, please consult the manual : [18717_XXX0_HAND.pdf](#)

DELTALIGHT

TGL-TR - SPY 27 92730

18717 9220 W

Notes: