

## DOT.COM M4 ST OK 93014

424 222 04 931 W-FG

AVAILABLE IN

**BLACK-BLACK** 424 222 04 931 B-B



**BLACK-CHROMED** 424 222 04 931 B-C

**BLACK-FLEMISH GOLD** 424 222 04 931 B-FG

**WHITE-BLACK** 424 222 04 931 W-B

**WHITE-CHROMED** 424 222 04 931 W-C

**WHITE-FLEMISH GOLD** 424 222 04 931 W-FG



 [View on website](#)



### General info

<b>LOCATION</b>	indoor
<b>INSTALLATION</b>	Ceiling Recessed
<b>CUTOUT SHAPE/SIZE (MM)</b>	rectangle - 136 x 40
<b>RECESSED DEPTH (MM)</b>	58
<b>THICKNESS OF MOUNTING SURFACE (MM)</b>	max.25
<b>INGRESS PROTECTION</b>	IP20
<b>WEIGHT (KG)</b>	0.3
<b>ADJUSTABILITY</b>	30° swiveling
<b>INFORMATION</b>	4 x REFLECTOR SP-14° EXCL.LED POWER SUPPLY 500mA-DC

### Electrical info

<b>CLASS</b>	III
<b>DIM TYPE</b>	depending on power supply
<b>ENERGY CLASS</b>	E
<b>CERTIFICATES</b>	CB, EAC, ENEC, LCA

### Lightsource info

<b>LIGHTSOURCE NAME</b>	LED
<b>LIGHTSOURCE</b>	LED cluster 5,7W / CRI>90 (R9: 50) / 3000K / 648lm
<b>TM-30 VALUES</b>	Rf: 90 / Rg: 101
<b>SDCM</b>	SDCM3
<b>RISKGROUP</b>	RG2
<b>LM80</b>	L80 > 60000
<b>BEAMANGLE</b>	14°
<b>LED TECHNICS (LIGHT SOURCE)</b>	648lm // 5,7W // 114lm/W
<b>LED TECHNICS (LUMINAIRE)</b>	473lm // 6,6W // 72lm/W

### Requirements

LED POWER SUPPLY 500mA-DC DIM


For detailed installation instructions, please consult the manual : [424\\_222\\_04\\_XXX\\_HAND.pdf](#)

# DELTALIGHT






**DOT.COM M4 ST OK 93014**

424 222 04 931 W-FG

## CEILING COMPATIBILITY

Ceiling Type	Mounting Kit
 System ceiling	-
 Plasterboard	-
 Stucanet	-
 Wood	-
 Stretched ceiling	-

## FINISH YOUR SPECIFICATION

LED power supplies	# of Fixtures
	Min current   Max current
<p> # of fixtures indicates how many devices can be connected (min -&gt; max) to the power supply. The values before and after the ' ' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.</p>	
 <p><b>300 48 500 ED1</b> LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM1</p> <p>Dimtype: 1-10V</p> <p>Cutout dimension (mm): 30</p>	3 <input type="text"/>
 <p><b>300 48 500 ED5</b> LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM5</p> <p>Dimtype: DALI</p> <p>Cutout dimension (mm): 45</p>	3 <input type="text"/>
 <p><b>300 48 500 MDL</b> LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W MDL</p> <p>Dimtype: non-dimmable</p> <p>Cutout dimension (mm): 30</p>	3 <input type="text"/>
 <p><b>300 48 500 WDL</b> LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W WDL</p> <p>Dimtype: WDL = wireless dimmable</p> <p>Cutout dimension (mm): 45</p>	3 <input type="text"/>

# DELTALIGHT

## DOT.COM M4 ST OK 93014

424 222 04 931 W-FG



**300 90 61** LED POWER SUPPLY MULTI-POWER DIM6

4

**Dimtype: mains (phase cut-off) or push button**

**Cutout dimension (mm): 56**



**300 90 63** LED POWER SUPPLY MULTI-POWER DIM9

6(6)

**Dimtype: 1-10V or DALI or push button**

**Cutout dimension (mm): 82**




**300 90 64** LED POWER SUPPLY MULTI-POWER DIM7

4(2)

**Dimtype: 1-10V or push button**

**Cutout dimension (mm): 72**




**300 90 68** LED POWER SUPPLY MULTI-POWER DIM5

4(2)

**Dimtype: DALI**

**Cutout dimension (mm): 72**



**300 90 69** LED POWER SUPPLY MULTI-POWER HV DIM9

9(7)

**Dimtype: 1-10V or DALI or push button**

**Cutout dimension (mm): 84**




**300 90 124** LED POWER SUPPLY MULTI-POWER DIM7

3(2)

**Dimtype: 1-10V or push button**

**Cutout dimension (mm): 55**




**300 90 125** LED POWER SUPPLY MULTI-POWER MINI DIM5

3(2)

**Dimtype: DALI**

**Cutout dimension (mm): 55**




**300 90 135** LED POWER SUPPLY MULTI-POWER HV

3->7

**Dimtype: non-dimmable**

**Cutout dimension (mm): 90**




**21012 0010** LED POWER SUPPLY MULTI POWER

3

**Dimtype: non-dimmable**

**Cutout dimension (mm): 50**



**21012 0021** LED POWER SUPPLY MULTI POWER DIM1

4


**Dimtype: 1-10V**

**Cutout dimension (mm): 54**

# DELTALIGHT

## DOT.COM M4 ST OK 93014

424 222 04 931 W-FG




**21012 0035** LED POWER SUPPLY MULTI POWER DIM5

4

**Dimtype: DALI**

**Cutout dimension (mm): 54**




**21012 004W** LED POWER SUPPLY MULTI-POWER WDL

6(6)

**Dimtype: WDL = wireless dimmable**

**Cutout dimension (mm): 84**




**21012 005W** LED POWER SUPPLY MULTI-POWER COMPACT WDL

4

**Dimtype: WDL = wireless dimmable**

**Cutout dimension (mm): 54**




**21012 0278** LED POWER SUPPLY MULTI POWER 500-700 / 20W DIM8

2->2

**Dimtype: mains (phase cut-off)**

**Cutout dimension (mm): 55**




**21012 0288** LED POWER SUPPLY MULTI POWER 500-700 / 36W DIM8

3->4

**Dimtype: mains (phase cut-off)**

**Cutout dimension (mm): 55**




**21012 0298** LED POWER SUPPLY MULTI POWER 250-900 / 20W DIM8

3

**Dimtype: mains (phase cut-off)**

**Cutout dimension (mm): 48**



**21032 0305** LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM5

3

**Dimtype: DALI**

**Cutout dimension (mm): 30**

Notes: