
DELTALIGHT




SOLI - FORM 90 DOWN-UP 2 CIRCUIT 92767 Q-DIM

REFERENCE 27147 922Q W-W

AVAILABLE IN
BLACK-BLACK 27147 922Q B-B
BLACK-FLEMISH GOLD 27147 922Q B-FG
WHITE-BLACK 27147 922Q W-B
WHITE-WHITE 27147 922Q W-W





View on website

General info	
LOCATION	indoor
INSTALLATION	Low voltage systems Low voltage system mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.7
ADJUSTABILITY	non adjustable
INFORMATION	INCL.36 x REFLECTOR FL-67° EXCL.LED POWER SUPPLY 48V-DC 2 CIRCUITS

Electrical info	
ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	Qbus dim
ENERGY CLASS	E
CERTIFICATES	CB, ENEC, LCA

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	DOWN: LED cluster 10,5W / CRI>90 (R9: 50) / 2700K / 1519lm UP: LED cluster 10,5W / CRI>90 (R9: 50) / 2700K / 1519lm
TM-30 VALUES	Rf: 93 / Rg: 100
SDCM	SDCM3
RISKGROUP	RG1
LM80	L80 > 60000
BEAMANGLE	67°
LED TECHNICS (LIGHT SOURCE)	DOWN: 1519lm // 10,5W // 144lm/W UP: 1519lm // 10,5W // 144lm/W
LED TECHNICS (LUMINAIRE)	DOWN: 1291lm // 12,1W // 107lm/W UP: 1018lm // 12,1W // 84lm/W

Requirements

LED POWER SUPPLY 48V-DC

For detailed installation instructions, please consult the manual : **27147_XXXQ_HAND.pdf**

DELTALIGHT

SOLI - FORM 90 DOWN-UP 2 CIRCUIT 92767 Q-DIM

27147 922Q W-W


FINISH YOUR SPECIFICATION

LED power supplies

of Fixtures


Min current | Max current

ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.




300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN — 4

Dimtype: non-dimmable



300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN — 10


Dimtype: non-dimmable



21012 0230 LED POWER SUPPLY 48V-DC / 100W — 4

Dimtype: non-dimmable

Cutout dimension (mm): 40



21012 0240 LED POWER SUPPLY 48V-DC / 200W — 8


Dimtype: non-dimmable

Cutout dimension (mm): 40


COMPATIBLE COMPOSABLES

SOLISCAPE profile

Available Colours



27111 0020 SOLI - PROFILE 2m



27111 0030 SOLI - PROFILE 3m

Notes:

SOLI - FORM 90 DOWN-UP 2 CIRCUIT 92767 Q-DIM

27147 922Q W-W