
DELTALIGHT




INFORM R4 C DOWN-UP 92748

REFERENCE 26826 9220 W-W

AVAILABLE IN
BLACK-BLACK 26826 9220 B-B
BLACK-FLEMISH GOLD 26826 9220 B-FG
FLEMISH GOLD-BLACK 26826 9220 FG-B
WHITE-BLACK 26826 9220 W-B
WHITE-WHITE 26826 9220 W-W





View on website

General info	
LOCATION	indoor
INSTALLATION	Ceiling Suspended
INGRESS PROTECTION	IP20
WEIGHT (KG)	2.2
ADJUSTABILITY	non adjustable
INFORMATION	96 x REFLECTOR WFL-71° (DOWN) EXCL.2 x LED POWER SUPPLY 700mA-DC (DOWN/UP) INCL.3 x CABLE SUSPENSION SINGLE AUTO. 1,6m INCL.1 x CABLE 5 x 0.75mm²

Electrical info	
CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	C
CERTIFICATES	CB, ENEC

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	DOWN: LED cluster 22,9W / CRI>90 (R9: 50) / 2700K / 3456lm UP: LED cluster 11,5W / CRI>90 (R9: 50) / 2700K / 1728lm
SDCM	SDCM3
LM80	L80 > 60000
BEAMANGLE	71°
LED TECHNICS (LIGHT SOURCE)	DOWN: 3456lm // 22,9W // 151lm/W UP: 1728lm // 11,5W // 151lm/W
LED TECHNICS (LUMINAIRE)	DOWN: 2761lm // 26,3W // 105lm/W UP: 1106lm // 13,2W // 84lm/W

Requirements

LED POWER SUPPLY 700mA-DC DIM (Remote)
INFORM R POWERBOX D/U DIM5

Options

CABLE BASE R / S
COVERSET R 62-90-100 / S 62-80-90
CONNECTION ST / CONNECTION TRIMLESS
SUSPENSION ST / SUSPENSION TRIMLESS

DELTALIGHT


INFORM R4 C DOWN-UP 92748

26826 9220 W-W

For detailed installation instructions, please consult the manual : **26826_XXX0_HAND.pdf**

FINISH YOUR SPECIFICATION

Current supply



203 99 55 ANO CABLE BASE R ANO ☐

203 99 55 B CABLE BASE R B ☐

203 99 55 W CABLE BASE R W ☐



203 99 56 ANO CABLE BASE S ANO ☐

203 99 56 B CABLE BASE S B ☐


203 99 56 W CABLE BASE S W ☐

Power box

of Fixtures

ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current



26810 0025 B INFORM R POWERBOX D/U DIM5 B 1 ☐

Dimtype: DALI

26810 0025 W INFORM R POWERBOX D/U DIM5 W 1 ☐

INFORM R4 C DOWN-UP 92748


26826 9220 W-W

LED power supplies

of Fixtures

Min current | Max current

ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.




300 90 64 LED POWER SUPPLY MULTI-POWER DIM7

1 down | 1 up ☐

Dimtype: 1-10V or push button

Cutout dimension (mm): 72




300 90 68 LED POWER SUPPLY MULTI-POWER DIM5

1 down | 1 up ☐

Dimtype: DALI

Cutout dimension (mm): 72


Coversets



204 00 62 ANO COVERSET R 62 ANO ☐

204 00 62 B COVERSET R 62 B ☐


204 00 62 W COVERSET R 62 W ☐



204 00 90 ANO COVERSET R 90 ANO ☐

204 00 90 B COVERSET R 90 B ☐

204 00 90 W COVERSET R 90 W ☐




204 00 100 ANO COVERSET R 100 ANO ☐

204 00 100 B COVERSET R 100 B ☐

204 00 100 W COVERSET R 100 W ☐

INFORM R4 C DOWN-UP 92748


26826 9220 W-W



204 62 62 ANO COVERSET S 62 ANO

204 62 62 B COVERSET S 62 B


204 62 62 W COVERSET S 62 W



204 80 80 ANO COVERSET S 80 ANO

204 80 80 B COVERSET S 80 B

204 80 80 W COVERSET S 80 W




204 90 90 ANO COVERSET S 90 ANO

204 90 90 B COVERSET S 90 B


204 90 90 W COVERSET S 90 W

Suspension parts



328 10 01 SUSPENSION TRIMLESS O.F.A.

Cutout dimension (mm): 62 (CONCRETE: 102)



15225 0340 B SUSPENSION ST B

Cutout dimension (mm): 27


15225 0340 W SUSPENSION ST W

DELTALIGHT

INFORM R4 C DOWN-UP 92748

26826 9220 W-W

Electric connection parts



328 10 03 CONNECTION TRIMLESS O.F.A. ☐

Cutout dimension (mm): 62 (CONCRETE: 102)



15225 0360 B CONNECTION ST B ☐

Cutout dimension (mm): 43

15225 0360 W CONNECTION ST W ☐

Notes: