

# SPLIT-IT - SPY 52, 66, & FOCUS



**Listing**  
ETL certified to US and Canadian safety standards.  
**Warranty**  
5-year limited warranty.

The Split-It made-to-measure lighting system integrates seamlessly with architecture and demonstrates that form and functionality in lighting have definitely gone down a new path, opening new ways to integrate "lighting paths" with architecture. The 37° knife-edge gives the appearance of a thin floating ceiling plane. Several corners and U-shaped returns help achieve clean cove installations. These high output aimable spots powered from above add to the versatility of the system.

Specification	Spy 52	Spy 66	Spy Focus
LED Aperture	2"	2 1/2"	2"
Adjustability:	Adjustable 0-90° / 355°		
Rating:	IP20		
Voltage:	48V		
Dimming:	Standard 0-10V dim 120-277V (1%)		
Power Supply:	96W, Constant Voltage driver with 0.9+ power factor and 90+% efficiency		

Performance	Static CCT (Spy 52)	Static CCT (Spy 66)	Static CCT (Spy Focus)
LED Maintenance:	L90>50,000h		
McAdam Step:	1		
CRI:	90+		
*SP:	10.2W	20W	10.2W
*HP:	14W		14W

Delivered Lumens	3000K		
**See page 3 for full details	NS	MD	WS
Spy 52 HP:	919Lm	936Lm	939Lm
Spy 52 SP:	681Lm	694Lm	700Lm
Spy 66 SP:	1500Lm	1478Lm	1442Lm
Spy Focus HP:	565Lm		

## Ordering

ALL BOXES MUST BE FILLED IN TO CORRECTLY ORDER

Example: SPY66MD-SP35A-B-GC-SPT-RMTD1

Luminaire	Size	Optic**	Power*	CCT	Function	Finish	Inner Finish <sup>(2)</sup>	Application <sup>(3)</sup>	Controls
SPY SPY	52 52mm / 2 1/16" Diameter	NS Narrow Spot 20° MD Medium Spot 30° WS Medium Wide Spot 45°	SP Standard Power  HP <sup>(1)</sup> High Power	27 2700K	A Adjustable	B Black W White	B <sup>(2)</sup> Black	SPT-RMT Split-It Profile Remote Power Supply	D1 0-10V dim 48V
	66 <sup>(1)</sup> 66mm / 2 10/32" Diameter	NS Narrow Spot 18° MD Medium Spot 30° WS Medium Wide Spot 45°		30 3000K			FBR <sup>(2)</sup> Flemish Bronze		
	FC FOCUS 62mm / 2 1/16" Diameter	FC Field Adjusted 8 - 43°		35 3500K			FG <sup>(2)</sup> Flemish Gold  GC <sup>(2)</sup> Gold Colored  W <sup>(2)</sup> White		

1 Spy 66 not available in Power HP.  
2 Does not apply to Spy Focus (Size FC); skip field.  
3 For use on Split-It Profile, specified separately.

## Related Products

Split-It Profile (hardware), Spy 52, Spy 66, Spy Focus  
Additional modules: Split-It Linear (page 5)

## Finish Options - Spy 52



### SPLIT-IT SPY 52



### SPY 52 INNER FINISH



## Accessories for Spy 52



Used solo with no  
other accessories

Used in combination with any  
other accessory; includes frame  
to hold this smaller honeycomb

## Finish Options - Spy 66


### SPLIT-IT SPY 66




### SPY 66 INNER FINISH




## Accessories for Spy 66



SPY 66 REFLECTOR 18°  
24611 0220



SPY 66 REFLECTOR 30°  
24611 0230




SPY 66 REFLECTOR 45°  
24611 0240




HONEYCOMB 57 SINGLE USE  
24611 0150 B

Used solo with no  
other accessories




HONEYCOMB 57 DOUBLE USE  
24611 0210 B


Used in combination with any  
other accessory; includes frame  
to hold this smaller honeycomb




LINEAR SPREAD LENS 57  
24611 0170



SOFTENING LENS 57  
24611 0190




SPREAD LENS 57  
24611 0200



GLASS SBL 57  
24611 0160

## Finish Options - Spy Focus


### SPLIT-IT SPY FOCUS




## Photometric Data - Spots

Delivered Lumens:	2700K			3000K			3500K		
Optic:	NS	MD	WS	NS	MD	WS	NS	MD	WS
Spy 52 HP:	879Lm	895Lm	898Lm	919Lm	936Lm	939Lm	952Lm	970Lm	972Lm
Spy 52 SP:	652Lm	664Lm	671Lm	681Lm	694Lm	700Lm	706Lm	719Lm	725Lm
Spy 66 SP:	1435Lm	1384Lm	1379Lm	1500Lm	14478Lm	1442Lm	1555Lm	1500Lm	1494Lm
Spy Focus HP:	540Lm			565Lm			585Lm		
Spy Focus SP:	399Lm			417Lm			432Lm		


### SPY 52



### SPY 66



### SPY FOCUS



## Installation Options

Delta Light's Magnetic Systems all utilize 48V remote power supplies. With a maximum of 96W per power supply, the below details maximum magnetic modules per power feed.

Maximum Capacity Per Power Supply	Spy 52	Spy 66	Spy Focus
*SP/HP:	8 / 5	4	8 / 5

FOR SYSTEM HARDWARE, REFER TO THE FOLLOWING PROFILE SYSTEMS:  
Split-It Profile

FOR DRIVER SPECS, REFER TO INSTALLATION / DRIVER OPTIONS ON  
PAGES 6 & 7 BELOW.

# SPLIT-IT - LED LINE



The Split-It made-to-measure lighting system integrates seamlessly with architecture and demonstrates that form and functionality in lighting have definitely gone down a new path, opening new ways to integrate "lighting paths" with architecture. The 37° knife-edge gives the appearance of a thin floating ceiling plane. Several corners and U-shaped returns help achieve clean cove installations. Options for indirect lighting in two different locations, depending on the desired effect, these linear uplight LED modules, and even high output aimable spots powered from above add to the versatility of the system.

Specification	
Adjustability:	Fixed
Rating:	IP20
Voltage:	24V
Dimming:	Standard 0-10V dim 120-277V (1%) FE ELV dim 120V (1%)
Power Supply:	96W, Constant Voltage driver with 0.9+ power factor and 90+% efficiency

Performance	Static CCT
LED Maintenance:	L70>40,000h
McAdam Step:	3
CRI:	80
*LED Line 01 SP:	2W
*LED Line 05 SP:	7W
*LED Line 10 SP:	25W

Delivered Lumens	3000K
LED Line 01:	247Lm
LED Line 05:	738Lm
LED Line 10:	1476Lm

## Listing

ETL certified to US and Canadian safety standards.

## Warranty

5-year limited warranty.

## Ordering

ALL BOXES MUST BE FILLED IN TO CORRECTLY ORDER

Example: LL10-SP30D-SPT-RMTD1




Luminaire	Size	Power*	CCT	Rating	Application <sup>(1)</sup>	Controls
LL LED LINE UPLIGHT MODULE	01 179mm / 7 <sup>1</sup> / <sub>16</sub> "	SP Standard Power	30 3000K	D Damp	SPT-RMT Split-It Profile Remote Power Supply	D1 0-10V dim 48V
	05 515mm / 2 <sup>1</sup> / <sub>4</sub> "					D8 FE ELV dim 120V
	10 1019mm / 40 <sup>1</sup> / <sub>8</sub> "					

<sup>1</sup> For use on Split It Profile, specified separately.


## Related Products

Split-It Profile, Spy 52, Spy 66, Spy Focus

Finish Options - Linear

LED LINE 01	LED LINE 05	LED LINE 10
		

Photometric Data - Linear



Installation Options

Delta Light's Split-It Profile utilizes 24V remote power supplies. With a maximum of 96W per power supply, the below details maximum modules per power feed.


Maximum capacity per power supply	LED line 01	LED line 05	LED line 10
*SP:	47	15	7

FOR SYSTEM HARDWARE, REFER TO THE FOLLOWING PROFILE:  
Split It Profile

REMOTE DRIVER (With Control D1 only)

**A:** 12" x **B:** 2"-7/8 x **C:** 4"-1/4  
**A:** 305mm x **B:** 72mm x **C:** 108mm


- For Remote application
- ETL Listed
- Damp rated



REMOTE DRIVER (With Control D8 only - only available for LED Line)

**A:** 12-1/8" x **B:** 1"-1/4 x **C:** 2"-3/8  
**A:** 307.34mm x **B:** 32.26mm x **C:** 59.94mm

- For Remote application
- ETL Listed
- Damp rated



## Driver Options

### D1

---

- Dimming Control 0-10V
- Dimming Range 1-100%
- Dim to off no
- Power Factor @ Full Load >0.97
- Efficiency @ Full Load  $\geq 89$

#### Dimmer Compatibility

- Leviton IP710-DLZ
- Lutron DDTV-XX

### D8

---

- Dimming Control Phase Control
- Dimming Range 1-100%
- Dim to off yes
- Power Factor @ Full Load >0.95
- Efficiency @ Full Load  $\geq 90$
- THD @ Full Load <10%

As technology changes, please use information above as guidance. For most recent updated information please contact factory. Specifications subject to change without notice.