



ENTERO RD-L TRIMLESS WALLWASH TW 965



28479 9000 B

AVAILABLE IN

BLACK 28479 9000 B

GOLD COLOURED 28479 9000 GC

WHITE 28479 9000 W



 [View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	round - Ø KIT
RECESSED DEPTH (MM)	165
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.67
ADJUSTABILITY	non adjustable
INFORMATION	REFLECTOR WALLWASH EXCL.LED POWER SUPPLY 500mA-DC TW - (DALI DT8)

Electrical info

CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	F
CERTIFICATES	CB, ENEC, EPD

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 17,8W / CRI>90 (R9: 50) / 2700K-6500K / 2054lm
TM-30 VALUES	rf: 89 / Rg: 100
SDCM	SDCM2
RISKGROUP	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	2054lm // 17,8W // 116lm/W
LED TECHNICS (LUMINAIRE)	1690lm // 20,5W // 83lm/W

Requirements

MOUNTING KIT ENTERO ROUND L
LED POWER SUPPLY 500mA-DC TW (Remote)
















For detailed installation instructions, please consult the manual : [28479_XXX0_HAND.pdf](#)

DELTALIGHT

ENTERO RD-L TRIMLESS WALLWASH TW 965

28479 9000 B


CEILING COMPATIBILITY

Ceiling Type	Mounting Kit	
 System ceiling	 28400 0030 - MOUNTING KIT ENTERO RD-L	Required
 Plasterboard	 28400 0030 - MOUNTING KIT ENTERO RD-L	Required
 Stucanet	 28400 0030 - MOUNTING KIT ENTERO RD-L	Required
 Concrete + plaster	 28400 0030 - MOUNTING KIT ENTERO RD-L	Required
 Lintel + plaster	 28400 0030 - MOUNTING KIT ENTERO RD-L	Required
 Hollow-core slab + plaster	 28400 0030 - MOUNTING KIT ENTERO RD-L	Required
 Stretched ceiling	 28400 0150 - MOUNTING KIT ENTERO RD-L WSC	Required
	 28400 0090 - MOUNTING KIT ENTERO RD-L CSC	Required


FINISH YOUR SPECIFICATION

LED power supplies

of Fixtures

 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current




21012 0355 LED POWER SUPPLY 500mA-DC 2CH TW DIM5

Dimtype: DALI

Cutout dimension (mm): 85

1

Mounting kits



28400 0030 MOUNTING KIT ENTERO RD-L


Cutout dimension (mm): 162

DELTALIGHT

ENTERO RD-L TRIMLESS WALLWASH TW 965

28479 9000 B

Mounting kits stretched ceiling



28400 0090 MOUNTING KIT ENTERO RD-L CSC



28400 0150 MOUNTING KIT ENTERO RD-L WSC



Notes: