



## OONO W S 930 DIM8

29611 9308 A

AVAILABLE IN

**ALU GREY** 29611 9308 A



**BLACK** 29611 9308 B

**FLEMISH BRONZE OUTDOOR** 29611 9308 FBRX

**GOLD MARBLED** 29611 9308 GM

**ANTHRACITE** 29611 9308 N

**WHITE** 29611 9308 W



[View on website](#)



### General info

|                                             |                                                                                            |
|---------------------------------------------|--------------------------------------------------------------------------------------------|
| <b>LOCATION</b>                             | indoor-outdoor                                                                             |
| <b>INSTALLATION</b>                         | Wall Surface mounted                                                                       |
| <b>INGRESS PROTECTION</b>                   | IP54                                                                                       |
| <b>PROTECTION AGAINST MECHANICAL IMPACT</b> | IK04                                                                                       |
| <b>WEIGHT (KG)</b>                          | 1.1                                                                                        |
| <b>ADJUSTABILITY</b>                        | non adjustable                                                                             |
| <b>INFORMATION</b>                          | INCL.DIMMABLE LED POWER SUPPLY 500mA-DC<br>GM (Gold Marbled) version only for interior use |

### Electrical info

|                     |                       |
|---------------------|-----------------------|
| <b>ELECTRICAL</b>   | 220-240V / 50-60Hz    |
| <b>CLASS</b>        | I                     |
| <b>POWER SUPPLY</b> | YES                   |
| <b>DIM TYPE</b>     | mains (phase cut-off) |
| <b>ENERGY CLASS</b> | E                     |

### Lightsource info

|                                    |                                                   |
|------------------------------------|---------------------------------------------------|
| <b>LIGHTSOURCE NAME</b>            | LED                                               |
| <b>LIGHTSOURCE</b>                 | LED array 8,6W / CRI>90 (R9: 52) / 3000K / 1089lm |
| <b>TM-30 VALUES</b>                | rf: 90 / Rg: 99                                   |
| <b>SDCM</b>                        | SDCM1                                             |
| <b>RISKGROUP</b>                   | RG1                                               |
| <b>LM80</b>                        | L90B10 > 50000                                    |
| <b>LED TECHNICS (LIGHT SOURCE)</b> | 1089lm // 8,6W // 127lm/W                         |
| <b>LED TECHNICS (LUMINAIRE)</b>    | 599lm // 9,9W // 61lm/W                           |

For detailed installation instructions, please consult the manual : [29611\\_XXX8\\_HAND.pdf](#)

Notes:

# DELTALIGHT

## **OONO W S 930 DIM8**

29611 9308 A