VISION



Since its launch Vision has won multiple awards, thanks to its impressive and nicely delineated parabolic light pattern on the wall. This classic is available both for indoor and outdoor use. Vision thanks its powerful light effect to the combination of LED technology in combination with a lens, giving its unique design.

Specification	
Installation Method	1/2" EMT or 4" junction box
Adjustability:	Fixed
Rating:	Damp (EU IP20)

Performance	
CRI / TM-30 (3000K):	80 / Rf: 86 / Rg: 95
McAdam Step:	3
LED Maintenance:	L90B10>150,000h
*Standard Power (SP):	2 x 1.2W
[1]Remote Power Supply Capacity (# luminaires) SP:	D1-UNV min2-max7 D8A-120 min2-max4
*Medium Power (MP):	2 x 1.6W
[1]Remote Power Supply Capacity (# luminaires) MP:	D1-UNV min2-max6 D8A-120 min3-max3 / D8B-120 min4-max6

Delivered Lumens	2700K	3000K
Vision SP:	185	185
Vision MP:	255	255

Listing
ETL certified to US and Canadian safety standards.

Warranty
5-year limited warranty.

Ordering
ALL BOXES MUST BE FILLED IN TO CORRECTLY ORDER

Example: VSN-SP30FI-W-MK-RMTD8-120

Luminaire	Power*	CCT	Function	Finish	Installation	Application	Controls***
VSN VISION	**SP** Standard Power	**27** 2700K	**FI** Fixed, Interior Use	**W-C** White-Chromed	**MK** Surface canopy with mud kit into drywall over 4" junction box	**RMT**[1] Remote Power Supply	**D1-UNV** 0-10V dim 120-277V
	MP Standard PowerN	**30** 3000K		**W** White	**NA** No optional accessory; utilizing 1/2" EMT install		**D8A-120** FE ELV dim 120V
							D8B-120[2] FE ELV dim 120V


1 Remote power supply capacity noted in table above.
2 Controls D8B-120 only available with Power MP.
*** Contact factory for additional dimming options.

Related Products

Tiga (wall), Mono (wall), Soiree (pendant), Miles (pendant), Spy C, Hedra C

Finish Options

VISION






WHITE-CHROMED



WHITE

Photometric Data

VISION




Installation Options

REMOTE DRIVER (With Controls D8)

A: 8″ x **B:** 2″-1/2 x **C:** 2″-1/2
A: 203mm x **B:** 64mm x **C:** 64mm


- For Remote application
- ETL Listed
- Damp rated




REMOTE DRIVER (With Controls D1)

A: 8″ x **B:** 2″-3/16 x **C:** 4″-1/4
A: 203mm x **B:** 72mm x **C:** 108mm

- For Remote application
- ETL Listed
- Damp rated



MK - MUDKIT 1



Requires 4" junction box

Driver Options

D1

- Dimming Control 0-10V
- Dimming Range 1-100%
- Dim to off yes at 0.7mA
- Power Factor @ Full Load >0.9
- Efficiency @ Full Load ≥87
- THD @ Full Load <20%
- Title 24 Compliant

Dimmer Compatibility

- Leviton IP710-DLZ
- Lutron DVTV-XX
- WattStopper ADF-120277
- Synergy Lighting Controls ISD BC

D8

- Dimming Control Phase Control
- Dimming Range 10-100%
- Dim to off no
- Power Factor @ Full Load >0.9
- Efficiency @ Full Load ≥78
- THD @ Full Load <12%

Dimmer Compatibility

- Leviton IPE04-1LZ
- Lutron DVELV-300P

As technology changes, please use information above as guidance. For most recent updated information please contact factory. Specifications subject to change without notice.