



VISION



Since its launch Vision has already won multiple awards, thanks to its impressive and nicely delineated parabolic light pattern on the wall. This classic is available in white and a clean white chromed. Vision thanks its powerful light effect to the combination of LED technology in combination with a lens, giving its unique design.

Specification	
Installation Method:	1/2" EMT or 4" J-Box
Adjustability:	Fixed
Rating:	IP20

Performance	
LED Maintenance:	L90>120,000h
McAdam Step:	3
CRI:	80
*SP:	2W
*MP:	2.8W

Delivered Lumens:	2700K	3000K
Vision SP:	185Lm	185Lm
Vision MP:	255Lm	255Lm

Listing

ETL certified to US and Canadian safety standards.

Warranty

5-year limited warranty.

Ordering

ALL BOXES MUST BE FILLED IN TO CORRECTLY ORDER

Example: VSN-SP27FI-W-MK-RMTD8-120

Luminaire	Power*	CCT	Function	Finish	Installation	Application	Controls***
VSN VISION	SP Standard Power	27 2700K	FI Fixed, Interior Use	W-C White-Chromed	MK Surface canopy with mud kit into drywall over 4" junction box	RMT Remote Power Supply	D1-UNV 0-10V dim 120-277V
	MP Medium Power	30 3000K		W White			NA No optional accessory; utilizing 1/2" EMT install

*** Contact factory for additional dimming options.

Related Products

Soiree, Miles, Spy C (pendant), Hedra C (pendant)




Finish Options

VISION



Photometric Data

VISION




Control Options

REMOTE DRIVER (With Controls D8)

A: 8" x B: 2"-1/2 x C: 2"-1/2
 A: 203mm x B: 64mm x C: 64mm


- For Remote application
- ETL Listed
- Damp rated




REMOTE DRIVER (With Controls D1)

A: 8" x B: 2"-3/16 x C: 4"-1/4
 A: 203mm x B: 72mm x C: 108mm

- For Remote application
- ETL Listed
- Damp rated



MK - MUDKIT 1



Requires 4" junction box



Driver Options

D1

- Dimming Control 0-10V
- Dimming Range 1-100%
- Dim to off yes at 0.7mA
- Power Factor @ Full Load >0.9
- Efficiency @ Full Load ≥87
- THD @ Full Load <20%
- Title 24 Compliant

Dimmer Compatibility

- Leviton IP710-DLZ
- Lutron DDTV-XX
- WattStopper ADF-120277
- Synergy Lighting Controls ISD BC

D8

- Dimming Control Phase Control
- Dimming Range 10-100%
- Dim to off no
- Power Factor @ Full Load >0.9
- Efficiency @ Full Load ≥78
- THD @ Full Load <1

Dimmer Compatibility

- Leviton IPE04-1LZ
- Lutron DVELV-300P

As technology changes, please use information above as guidance. For most recent updated information please contact factory. Specifications subject to change without notice.