
DELTALIGHT




SUPERNOVA FLAT 95 PRISMATIC DOWN-UP 930 DIM1

REFERENCE 20615 9301 B

AVAILABLE IN
BLACK 20615 9301 B
WHITE 20615 9301 W





View on website

General info	
LOCATION	indoor
INSTALLATION	Ceiling Suspended
INGRESS PROTECTION	IP20
WEIGHT (KG)	12.7
ADJUSTABILITY	non adjustable
INFORMATION	INCL.PC PRISMATIC INCL.DIMMABLE LED POWER SUPPLY 1860mA (DOWN) / 500mA (UP)

Electrical info	
ELECTRICAL	220-240V / 0|50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	1-10V
ENERGY CLASS	D
CERTIFICATES	CB, ENEC, LCA, RCM

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	DOWN @ 1860mA: LED cluster 79,4W / CRI>90 (R9: 68) / 3000K / 11477lm UP @ 500mA: 2 x (LED cluster 11,1W / CRI>90 (R9: 50) / 3000K / 1487lm)
TM-30 VALUES	Rf: 89 / Rg: 97 Rf: 92 / Rg: 100
SDCM	SDCM3
RISKGROUP	RG1
LM80	L70 > 60000 L80 > 60000
LED TECHNICS (LIGHT SOURCE)	DOWN @ 1860mA: 11477lm // 79,4W // 144lm/W UP @ 500mA: 2974lm // 22,2W // 134lm/W
LED TECHNICS (LUMINAIRE)	DOWN @ 1860mA: 8585lm // 91,3W // 94lm/W UP @ 500mA: 2784lm // 25,5W // 109lm/W

Requirements

SUSPENSION SET 25 DIM 3m
CENTRAL ROD SUSPENSION SUPERNOVA FLAT 1m
CENTRAL SUSPENSION SUPERNOVA FLAT

Options

CABLE BASE R / S
COVERSET R 62-90-100 / S 62-80-90


SUPERNOVA FLAT 95 PRISMATIC DOWN-UP 930 DIM1

20615 9301 B

For detailed installation instructions, please consult the manual : **20615_XXX1_HAND.pdf**

FINISH YOUR SPECIFICATION

Current supply



203 99 55 ANO CABLE BASE R ANO

203 99 55 B CABLE BASE R B

203 99 55 W CABLE BASE R W




203 99 56 ANO CABLE BASE S ANO

203 99 56 B CABLE BASE S B

203 99 56 W CABLE BASE S W


Coversets



204 00 62 ANO COVERSET R 62 ANO

204 00 62 B COVERSET R 62 B

204 00 62 W COVERSET R 62 W







204 00 90 ANO COVERSET R 90 ANO

DELTALIGHT

SUPERNOVA FLAT 95 PRISMATIC DOWN-UP 930 DIM1

20615 9301 B


	204 00 90 B	COVERSET R 90 B	☐
	204 00 90 W	COVERSET R 90 W	☐
	**204 00 100 ANO**	COVERSET R 100 ANO	☐
	204 00 100 B	COVERSET R 100 B	☐
	204 00 100 W	COVERSET R 100 W	☐
	**204 62 62 ANO**	COVERSET S 62 ANO	☐
	204 62 62 B	COVERSET S 62 B	☐
	204 62 62 W	COVERSET S 62 W	☐
	**204 80 80 ANO**	COVERSET S 80 ANO	☐
	204 80 80 B	COVERSET S 80 B	☐
	204 80 80 W	COVERSET S 80 W	☐
	**204 90 90 ANO**	COVERSET S 90 ANO	☐
	204 90 90 B	COVERSET S 90 B	☐
	204 90 90 W	COVERSET S 90 W	☐

DELTALIGHT

SUPERNOVA FLAT 95 PRISMATIC DOWN-UP 930 DIM1


20615 9301 B

Suspension parts




274 97 10 B CENTRAL ROD SUSPENSION SUPERNOVA FLAT 1m B ☐

274 97 10 W CENTRAL ROD SUSPENSION SUPERNOVA FLAT 1m W ☐



328 25 43 ED SUSPENSION SET 25 DIM 3m ☐



328 26 23 B CENTRAL SUSPENSION SUPERNOVA FLAT 3m B ☐

328 26 23 W CENTRAL SUSPENSION SUPERNOVA FLAT 3m W ☐

Electric connection parts



15225 0360 B CONNECTION ST B ☐

Cutout dimension (mm): 43

15225 0360 W CONNECTION ST W ☐

Notes: