




SL19 - SPY 39 92720 DIM5

27025 9225 GC

AVAILABLE IN
BLACK 27025 9225 B
FLEMISH BRONZE 27025 9225 FBR
FLEMISH GOLD 27025 9225 FG
GOLD COLOURED 27025 9225 GC
WHITE 27025 9225 W



 [View on website](#)



General info	
LOCATION	indoor
INSTALLATION	Low voltage systems Low voltage system mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.3
ADJUSTABILITY	0° to 85° swiveling, 355° rotatable
INFORMATION	REFLECTOR FL-20° EXCLLED POWER SUPPLY 48V-DC
Electrical info	
ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	DALI
ENERGY CLASS	E
CERTIFICATES	CB, ENEC
Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 8,6W / CRI>90 (R9: 60) / 2700K / 1041lm
TM-30 VALUES	Rf: 89 / Rg: 100
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	20°
LED TECHNICS (LIGHT SOURCE)	1041lm // 8,6W // 121lm/W
LED TECHNICS (LUMINAIRE)	849lm // 9,9W // 86lm/W

Requirements
SPY 39 TUBE or VISOR 39
LED POWER SUPPLY 48V-DC

For detailed installation instructions, please consult the manual : [27025_XXX5_HAND.pdf](#)

FINISH YOUR SPECIFICATION


LED power supplies

of Fixtures



of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.


Min current | Max current



300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN

10


Dimtype: non-dimmable



300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN

24

Dimtype: non-dimmable




21012 0230 LED POWER SUPPLY 48V-DC / 100W

10

Dimtype: non-dimmable

Cutout dimension (mm): 40




21012 0240 LED POWER SUPPLY 48V-DC / 200W

20

Dimtype: non-dimmable


Cutout dimension (mm): 40

Light altering devices



24144 0030 B VISOR 39 B

Finish your product





24144 0010 B SPY 39 TUBE B

24144 0010 FBR SPY 39 TUBE FBR



DELTALIGHT

SL19 - SPY 39 92720 DIM5

27025 9225 GC

	SPY 39 TUBE FG	☐
	SPY 39 TUBE GC	☐
	SPY 39 TUBE W	☐
	SPY 39 TUBE SBL	☐

COMPATIBLE COMPOSABLES

SHIFTLINE 19 profile	Available Colours
 27011 0050 SL19 - PROFILE 2m	 
 27011 0060 SL19 - PROFILE 3m	 

Notes: