DELTALIGHT



# LOGIC LINEAR 440 HONEYCOMB 93040 DIM5

**REFERENCE** 30812 9335 N

AVAILABLE IN
**ANTHRACITE** 30812 9335 N







View on website

| General info | |
|---|---|
| **LOCATION** | outdoor |
| **INSTALLATION** | Floor Recessed |
| **CUTOUT SHAPE/SIZE (MM)** | rectangle - BOX |
| **RECESSED DEPTH (MM)** | 140 |
| **INGRESS PROTECTION** | IP67 |
| **PROTECTION AGAINST MECHANICAL IMPACT** | IK09 |
| **WEIGHT (KG)** | 2 |
| **ADJUSTABILITY** | non adjustable |
| **INFORMATION** | 8 x LENS WFL-40°<br>INCL.HONEYCOMB<br>INCL.DIMMABLE LED POWER SUPPLY 650mA-DC<br>INCL.1 x CABLE H07 RN-F 5 x 1mm² 0,5m<br>INCL.IP68 CONNECTOR 5P<br>ESG 8mm max.500kg |

| Electrical info | |
|---|---|
| **ELECTRICAL** | 220-240V / 0\|50-60Hz |
| **CLASS** | I |
| **POWER SUPPLY** | YES |
| **DIM TYPE** | DALI |
| **ENERGY CLASS** | E |
| **CERTIFICATES** | CB, ENEC, EPD, RCM |

| Lightsource info | |
|---|---|
| **LIGHTSOURCE NAME** | LED |
| **LIGHTSOURCE** | LED cluster 14,4W / CRI>90 (R9: 64) / 3000K / 1798lm |
| **TM-30 VALUES** | Rf: 92 / Rg: 99 |
| **SDCM** | SDCM3 |
| **RISKGROUP** | RG2 |
| **LM80** | L80 > 150000 |
| **BEAMANGLE** | 40° |
| **LED TECHNICS (LIGHT SOURCE)** | 1798lm // 14,4W // 121lm/W |
| **LED TECHNICS (LUMINAIRE)** | 702lm // 17W // 42lm/W |

**Requirements**

LOGIC LINEAR BOX

DELTALIGHT

# LOGIC LINEAR 440 HONEYCOMB 93040 DIM5

30812 9335 N

For detailed installation instructions, please consult the manual : **30812_XXX5_HAND.pdf**

## FINISH YOUR SPECIFICATION

### Ground mounting boxes



**30810 0010** LOGIC LINEAR 440 BOX ☐

**Cutout dimension (mm): 480 x 150**

### Waterproof connection parts



**21034 0150** IP68 Y-CONNECTOR 5P ☐

Notes: