
DELTALIGHT




MICROSPY IN 93030

REFERENCE 24110 9320 W

AVAILABLE IN
BLACK 24110 9320 B
WHITE 24110 9320 W





View on website

General info	
LOCATION	indoor
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	round - 36
RECESSED DEPTH (MM)	75
THICKNESS OF MOUNTING SURFACE (MM)	min.2 - max.25
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.1
ADJUSTABILITY	non adjustable
INFORMATION	LENS FL-30° EXCL.LED POWER SUPPLY 350-450mA-DC

Electrical info	
CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	F
CERTIFICATES	CB, EAC, ENEC

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 3,9-5,1W / CRI>90 (R9: 55) / 3000K / 385-480lm
TM-30 VALUES	Rf: 92 / Rg: 98
SDCM	SDCM2
RISKGROUP	RG2 (threshold 0,6m)
LM80	L90B10 > 41000
BEAMANGLE	30°
LED TECHNICS (LIGHT SOURCE)	480lm // 5,1W // 94lm/W
LED TECHNICS (LUMINAIRE)	376lm // 6W // 64lm/W

Requirements

LED POWER SUPPLY 350 / 450mA-DC DIM

For detailed installation instructions, please consult the manual : **24110_XXXX_HAND.pdf**

MICROSPY IN 93030

24110 9320 W

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit
 **System ceiling**	-
 **Plasterboard**	-
 **Stucanet**	-
 **Wood**	-
 **Concrete**	-
 **Concrete + plaster**	-
 **Lintel + plaster**	-
 **Hollow-core slab + plaster**	-
 **Stretched ceiling**	-


FINISH YOUR SPECIFICATION

LED power supplies

# of Fixtures

Min current | Max current


ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.



300 48 350 ED1 LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM1 — 3 ☐

Dimtype: 1-10V

Cutout dimension (mm): 30




300 48 350 ED5 LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5 — 3 ☐

Dimtype: DALI

Cutout dimension (mm): 45

MICROSPY IN 93030


24110 9320 W



300 48 350 MDL LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W MDL — 3

Dimtype: non-dimmable


Cutout dimension (mm): 30



300 48 350 WDL LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W WDL — 3

Dimtype: WDL = wireless dimmable


Cutout dimension (mm): 45



300 90 61 LED POWER SUPPLY MULTI-POWER DIM6 — 3 | - | -

Dimtype: mains (phase cut-off) or push button


Cutout dimension (mm): 56



300 90 63 LED POWER SUPPLY MULTI-POWER DIM9 — 6(6) | -

Dimtype: 1-10V or DALI or push button


Cutout dimension (mm): 82



300 90 64 LED POWER SUPPLY MULTI-POWER DIM7 — 4(3) | - | -


Dimtype: 1-10V or push button

Cutout dimension (mm): 72



300 90 67 LED POWER CONVERTER 24V-DC TO MULTI CURRENT 48W DIM9 — 3 | - | -


Dimtype: 1-10V or DALI or push button



300 90 68 LED POWER SUPPLY MULTI-POWER DIM5 — 3(3) | - | -

Dimtype: DALI


Cutout dimension (mm): 72



300 90 69 LED POWER SUPPLY MULTI-POWER HV DIM9 — 2->9(10) | 2->9(4)

Dimtype: 1-10V or DALI or push button


Cutout dimension (mm): 84



300 90 91 LED POWER SUPPLY 350mA-DC / 15W — 3(2)

Dimtype: non-dimmable

Cutout dimension (mm): 40




300 90 108 LED POWER SUPPLY 350mA-DC / 8W — 1

Dimtype: non-dimmable

Cutout dimension (mm): 40

MICROSPY IN 93030

24110 9320 W



300 90 110 LED POWER SUPPLY 350mA-DC / 10W DIM8 2->2

Dimtype: mains (phase cut-off)


Cutout dimension (mm): 42



300 90 116 LED POWER SUPPLY 350mA-DC / 18W DIM8 3->4

Dimtype: mains (phase cut-off)


Cutout dimension (mm): 55



300 90 124 LED POWER SUPPLY MULTI-POWER DIM7 2->4(3) | 3(2)

Dimtype: 1-10V or push button


Cutout dimension (mm): 55



300 90 125 LED POWER SUPPLY MULTI-POWER MINI DIM5 4(3) | 3(2)

Dimtype: DALI


Cutout dimension (mm): 55



300 90 134 LED POWER SUPPLY MULTI-POWER HV DIM7 2->8(8) | - | -

Dimtype: 1-10V or push button


Cutout dimension (mm): 84



300 90 135 LED POWER SUPPLY MULTI-POWER HV 4->6 | - | -

Dimtype: non-dimmable


Cutout dimension (mm): 90



300 90 3112 LED POWER SUPPLY 350mA-DC / 16W DIM8 2->3

Dimtype: mains (phase cut-off)


Cutout dimension (mm): 43



21012 004W LED POWER SUPPLY MULTI-POWER WDL 5(5) | - | -

Dimtype: WDL = wireless dimmable


Cutout dimension (mm): 84



21012 005W LED POWER SUPPLY MULTI-POWER COMPACT WDL 4 | -

Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 54



21012 0298 LED POWER SUPPLY MULTI POWER 250-900 / 20W DIM8 3 | 3


Dimtype: mains (phase cut-off)

Cutout dimension (mm): 48

DELTALIGHT

MICROSPY IN 93030


24110 9320 W



21012 0480 LED POWER SUPPLY 350mA-DC / 17W IP68 4(3)

Dimtype: non-dimmable

Cutout dimension (mm): 60



21032 0295 LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5 3

Dimtype: DALI

Cutout dimension (mm): 30

Notes: