



ENTERO RD-S TRIMLESS WALLWASH TW 965


28466 9000 B

AVAILABLE IN

BLACK 28466 9000 B

GOLD COLOURED 28466 9000 GC

WHITE 28466 9000 W



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	round - Ø KIT
RECESSED DEPTH (MM)	95
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.14
ADJUSTABILITY	non adjustable
INFORMATION	REFLECTOR WALLWASH EXCL.LED POWER SUPPLY 500mA-DC TW - (DALI DT8)

Electrical info

CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	E
CERTIFICATES	CB, ENEC, EPD

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 9W / CRI>90 (R9: 50) / 2700K-6500K / 1087lm
TM-30 VALUES	rf: 89 / Rg: 100
SDCM	SDCM2
RISKGROUP	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	1087lm // 9W // 121lm/W
LED TECHNICS (LUMINAIRE)	884lm // 10,4W // 85lm/W

Requirements

MOUNTING KIT ENTERO ROUND S

MOUNTING KIT AIR 105

LED POWER SUPPLY 500mA-DC TW (Remote)

For detailed installation instructions, please consult the manual : [28466_XXX0_HAND.pdf](#)

ENTERO RD-S TRIMLESS WALLWASH TW 965

28466 9000 B

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit		
 System ceiling		28400 0010 - MOUNTING KIT ENTERO RD-S O.F.A.	Required
 Plasterboard		28400 0010 - MOUNTING KIT ENTERO RD-S O.F.A.	Required
 Stucanet		28400 0010 - MOUNTING KIT ENTERO RD-S O.F.A.	Required
 Concrete + plaster		28400 0010 - MOUNTING KIT ENTERO RD-S O.F.A.	Required
 Lintel + plaster		28400 0010 - MOUNTING KIT ENTERO RD-S O.F.A.	Required
 Hollow-core slab + plaster		28400 0010 - MOUNTING KIT ENTERO RD-S O.F.A.	Required
 Stretched ceiling		28400 0070 - MOUNTING KIT ENTERO RD-S CSC	Required
		28400 0130 - MOUNTING KIT ENTERO RD-S WSC	Required
 Ventilation in plasterboard		29810 0100 - MOUNTING KIT SIDE AIR ONLY 1	Required
		29810 0110 - MOUNTING KIT SIDE AIR 105	Required
		29810 0120 - MOUNTING KIT NO AIR 105	Required
 Ventilation in concrete + plaster		29810 0120 - MOUNTING KIT NO AIR 105	Required
		29810 0130 - MOUNTING KIT TOP AIR 105	Required
		29810 0200 - MOUNTING KIT TOP AIR ONLY 1	Required


FINISH YOUR SPECIFICATION

LED power supplies

of Fixtures

 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current



21012 0355 LED POWER SUPPLY 500mA-DC 2CH TW DIM5

Dimtype: DALI

Cutout dimension (mm): 85


2

DELTALIGHT

ENTERO RD-S TRIMLESS WALLWASH TW 965

28466 9000 B

Mounting kits




28400 0010 MOUNTING KIT ENTERO RD-S O.F.A.

☐

Cutout dimension (mm): 105

Mounting kits stretched ceiling




28400 0070 MOUNTING KIT ENTERO RD-S CSC

☐

28400 0130 MOUNTING KIT ENTERO RD-S WSC

☐

Mounting kits side air + light




29810 0110 MOUNTING KIT SIDE AIR 105

☐

Cutout dimension (mm): 168

Mounting kits top air + light




29810 0130 MOUNTING KIT TOP AIR 105

☐

Cutout dimension (mm): 135

Mounting kits side air only



29810 0100 MOUNTING KIT SIDE AIR ONLY 1

☐


Cutout dimension (mm): 168

DELTALIGHT

ENTERO RD-S TRIMLESS WALLWASH TW 965

28466 9000 B

Mounting kits top air only




29810 0200 MOUNTING KIT TOP AIR ONLY 1

Cutout dimension (mm): 135



Mounting kits no air



29810 0120 MOUNTING KIT NO AIR 105

Cutout dimension (mm): 168



Notes: