





SPY 66 93018 ADM SLIM

24626 9310 B

AVAILABLE IN
NOIR 24626 9310 B
BLANC 24626 9310 W



[View on website](#)



General info

LOCATION	interieur
INSTALLATION	Rail Monté sur rail
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.6
ADJUSTABILITY	0° à 90° inclinable, 360° rotatif
INFORMATION	REFLECTOR SP-18° 3F MULTI POWER SLIM ADAPTER 350-700mA Current selection via jumper on adapter Optional REFLECTORS 30° & 45° available

Electrical info

ELECTRICAL	220-240V / 50-60Hz
CLASS	II
POWER SUPPLY INCLUDED	YES
DIM TYPE	non dimmable
ENERGY CLASS	E
CERTIFICATION	CB, RCM

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 25W / CRI>90 (R9: 52) / 3000K / 281lm
RVALUES	rf: 90 / Rg: 99
SDMC	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	18°
LED TECHNICS (LIGHT SOURCE)	281lm // 25W // 112lm/W
LED TECHNICS (LUMINAIRE)	2007lm // 28,8W // 70lm/W

Requirements

SPY 66 TUBE
 TRACK 3F DIM

Accessories

HONEYCOMB 57

For detailed installation instructions, please consult the manual : [24626_XXX0_HAND.pdf](#)

FINISH YOUR SPECIFICATION


modifier les dispositifs de lumière



24611 0150 B HONEYCOMB 57 SINGLE USE B

☐

Terminez votre produit



24611 0100 B SPY 66 TUBE B

☐

24611 0100 FBR SPY 66 TUBE FBR

☐

24611 0100 FG SPY 66 TUBE FG

☐

24611 0100 GC SPY 66 TUBE GC

☐

24611 0100 W SPY 66 TUBE W

☐

Réflecteur / lentille remplaçable



24611 0220 SPY 66 REFLECTOR 18°

☐

24611 0230 SPY 66 REFLECTOR 30°

☐

24611 0240 SPY 66 REFLECTOR 45°

☐

COMPATIBLE TRACKS

TRACK 3F DIM H			Available Colours
200 14 410	TRACK 3F DIM H 1m	1000 m 1.6 kg	
200 14 420	TRACK 3F DIM H 2m	2000 m 3.2 kg	
200 14 430	TRACK 3F DIM H 3m	3000 m 4.8 kg	
TRACK 3F DIM IN			Available Colours
200 13 410	TRACK 3F DIM IN 1m	1000 m 1.2 kg	
200 13 420	TRACK 3F DIM IN 2m	2000 m 2.4 kg	
200 13 430	TRACK 3F DIM IN 3m	3000 m 3.5 kg	
TRACK 3F DIM ON			Available Colours
200 12 410	TRACK 3F DIM ON 1m	1000 m 1.1 kg	
200 12 420	TRACK 3F DIM ON 2m	2000 m 2.1 kg	
200 12 430	TRACK 3F DIM ON 3m	3000 m 3.1 kg	

Notes: