




OONO W S 930 DIM8

29611 9308 N

AVAILABLE IN

ALU GREY 29611 9308 A


BLACK 29611 9308 B

FLEMISH BRONZE OUTDOOR 29611 9308 FBRX

GOLD MARBLED 29611 9308 GM

ANTHRACITE 29611 9308 N

WHITE 29611 9308 W



[View on website](#)



General info

LOCATION	indoor-outdoor
INSTALLATION	Wall Surface mounted
INGRESS PROTECTION	IP54
PROTECTION AGAINST MECHANICAL IMPACT	IK04
WEIGHT (KG)	1.1
ADJUSTABILITY	non adjustable
INFORMATION	INCL.DIMMABLE LED POWER SUPPLY 500mA-DC GM (Gold Marbled) version only for interior use

Electrical info

ELECTRICAL	220-240V / 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	mains (phase cut-off)
ENERGY CLASS	E

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 8,6W / CRI>90 (R9: 52) / 3000K / 1089lm
TM-30 VALUES	rf: 90 / Rg: 99
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	1089lm // 8,6W // 127lm/W
LED TECHNICS (LUMINAIRE)	599lm // 9,9W // 61lm/W

For detailed installation instructions, please consult the manual : [29611_XXX8_HAND.pdf](#)

Notes:

DELTALIGHT

OONO W S 930 DIM8

29611 9308 N