





SUPER-OH! XS 39 DIM8

308 21 03 83 ED8 W

AVAILABLE IN

BLACK 308 21 03 83 ED8 B

WHITE 308 21 03 83 ED8 W



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Surface mounted, Wall Surface mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	1.1
ADJUSTABILITY	non adjustable
INFORMATION	INCL.PC SBL

Electrical info

ELECTRICAL	220-240V / 50-60Hz
CLASS	II
POWER SUPPLY	YES
DIM TYPE	mains (phase cut-off)
ENERGY CLASS	E

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 25W / CRI>80 / 3000K / 2940lm
LED TECHNICS (LIGHT SOURCE)	2940lm // 25W // 118lm/W
LED TECHNICS (LUMINAIRE)	1396lm // 28,8W // 49lm/W

For detailed installation instructions, please consult the manual : [308 21 03 XX ED8 HAND.pdf](#)

FINISH YOUR SPECIFICATION

Miscellaneous control equipment

of Fixtures




of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the 'I' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current

DELTALIGHT

SUPER-OH! XS 39 DIM8

308 21 03 83 ED8 W




300 90 004 ED8 WIRELESS CONTROL DIM8



Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 40



300 90 126 FALLING EDGE DIMMER 200W DIM2



Dimtype: DALI or push button

Cutout dimension (mm): 67

Notes: