
DELTALIGHT




INFORM R1 DOWN-UP 93048

REFERENCE 26812 9320 W-W

AVAILABLE IN
BLACK-BLACK 26812 9320 B-B
BLACK-FLEMISH GOLD 26812 9320 B-FG
FLEMISH GOLD-BLACK 26812 9320 FG-B
WHITE-BLACK 26812 9320 W-B
WHITE-WHITE 26812 9320 W-W





View on website

General info	
LOCATION	indoor
INSTALLATION	Ceiling Suspended
INGRESS PROTECTION	IP20
WEIGHT (KG)	2.2
ADJUSTABILITY	non adjustable
INFORMATION	96 x REFLECTOR WFL-71° (DOWN) EXCL.LED 2 x POWER SUPPLY 700mA-DC (DOWN/UP) INCL.4 x CABLE SUSPENSION SINGLE AUTO. 1,6m INCL.1 x CABLE 5 x 0.75mm²

Electrical info	
CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	C
CERTIFICATES	CB, ENEC

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	DOWN: LED cluster 22,9W / CRI>90 (R9: 50) / 3000K / 3504lm UP: LED cluster 11,5W / CRI>90 (R9: 50) / 3000K / 1752lm
SDCM	SDCM3
LM80	L80 > 60000
BEAMANGLE	71°
LED TECHNICS (LIGHT SOURCE)	DOWN: 3504lm // 22,9W // 153lm/W UP: 1752lm // 11,5W // 153lm/W
LED TECHNICS (LUMINAIRE)	DOWN: 2800lm // 26,3W // 106lm/W UP: 1121lm // 13,2W // 85lm/W

Requirements

LED POWER SUPPLY 700mA-DC DIM (Remote)

Options

CABLE BASE R / S
COVERSET R 62-90-100 / S 62-80-90
CONNECTION ST / CONNECTION TRIMLESS
SUSPENSION ST / SUSPENSION TRIMLESS

DELTALIGHT


INFORM R1 DOWN-UP 93048

26812 9320 W-W

For detailed installation instructions, please consult the manual : **26812_XXX0_HAND.pdf**

FINISH YOUR SPECIFICATION

Current supply



203 99 55 ANO CABLE BASE R ANO ☐

203 99 55 B CABLE BASE R B ☐

203 99 55 W CABLE BASE R W ☐



203 99 56 ANO CABLE BASE S ANO ☐

203 99 56 B CABLE BASE S B ☐


203 99 56 W CABLE BASE S W ☐

LED power supplies

of Fixtures

ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.


Min current | Max current



300 90 64 LED POWER SUPPLY MULTI-POWER DIM7 — 1 down | 1 up ☐

Dimtype: 1-10V or push button

Cutout dimension (mm): 72



300 90 68 LED POWER SUPPLY MULTI-POWER DIM5 — 1 down | 1 up ☐






Dimtype: DALI

Cutout dimension (mm): 72

INFORM R1 DOWN-UP 93048


26812 9320 W-W

Coversets



	**204 00 62 ANO**	COVERSET R 62 ANO
	204 00 62 B	COVERSET R 62 B
	204 00 62 W	COVERSET R 62 W
	**204 00 90 ANO**	COVERSET R 90 ANO
	204 00 90 B	COVERSET R 90 B
	204 00 90 W	COVERSET R 90 W
	**204 00 100 ANO**	COVERSET R 100 ANO
	204 00 100 B	COVERSET R 100 B
	204 00 100 W	COVERSET R 100 W
	**204 62 62 ANO**	COVERSET S 62 ANO
	204 62 62 B	COVERSET S 62 B
	204 62 62 W	COVERSET S 62 W
	**204 80 80 ANO**	COVERSET S 80 ANO
	204 80 80 B	COVERSET S 80 B

INFORM R1 DOWN-UP 93048



26812 9320 W-W

	204 80 80 W COVERSET S 80 W	☐
	**204 90 90 ANO** COVERSET S 90 ANO	☐
	204 90 90 B COVERSET S 90 B	☐
	204 90 90 W COVERSET S 90 W	☐

Suspension parts

	**328 10 01** SUSPENSION TRIMLESS O.F.A. **Cutout dimension (mm): 62 (CONCRETE: 102)**	☐
	**15225 0340 B** SUSPENSION ST B **Cutout dimension (mm): 27**	☐
	15225 0340 W SUSPENSION ST W	☐

Electric connection parts

	**328 10 03** CONNECTION TRIMLESS O.F.A. **Cutout dimension (mm): 62 (CONCRETE: 102)**	☐
	**15225 0360 B** CONNECTION ST B **Cutout dimension (mm): 43**	☐
	15225 0360 W CONNECTION ST W	☐

INFORM R1 DOWN-UP 93048

26812 9320 W-W

Notes: