



SL19 - SPY 20 L 93030 MDL

REFERENCE

27028 9320 GC

AVAILABLE IN



BLACK 27028 9320 B

FLEMISH BRONZE 27028 9320 FBR

FLEMISH GOLD 27028 9320 FG

GOLD COLOURED 27028 9320 GC

WHITE 27028 9320 W



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Low voltage systems Low voltage system mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.1
ADJUSTABILITY	0° to 90° swiveling, 355° rotatable
INFORMATION	REFLECTOR FL-30° EXCLLED POWER SUPPLY 48V-DC SPY 20 TUBE B included

Electrical info

ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	MDL = 1-10V or DALI or push button
ENERGY CLASS	E
CERTIFICATES	CB, ENEC

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 2W / CRI>90 (R9: 60) / 3000K / 240lm
TM-30 VALUES	Rf: 91 / Rg: 101
SDCM	SDCM3
RISKGROUP	RG2
LM80	L90B10 > 150000
BEAMANGLE	30°
LED TECHNICS (LIGHT SOURCE)	240lm // 2W // 120lm/W
LED TECHNICS (LUMINAIRE)	181lm // 2,3W // 79lm/W

Requirements

LED POWER SUPPLY 48V-DC

Options

DIMMABLE MODULATOR

For detailed installation instructions, please consult the manual : [27028_XXX0_HAND.pdf](#)

FINISH YOUR SPECIFICATION


SMART 48

of Fixtures



of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.


Min current | Max current



300 90 011 SMART 48 MODULATOR DIM9

72

Dimtype: 1-10V or DALI or push button



300 90 012 SMART 48 MODULATOR WD

72

Dimtype: WDL = wireless dimmable


LED power supplies

of Fixtures



of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.


Min current | Max current



300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN

37


Dimtype: non-dimmable



300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN

90

Dimtype: non-dimmable




21012 0230 LED POWER SUPPLY 48V-DC / 100W

37

Dimtype: non-dimmable

Cutout dimension (mm): 40



21012 0240 LED POWER SUPPLY 48V-DC / 200W

75

Dimtype: non-dimmable



Cutout dimension (mm): 40

DELTALIGHT

SL19 - SPY 20 L 93030 MDL

27028 9320 GC

COMPATIBLE COMPOSABLES

SHIFTLINE 19 profile	Available Colours
 27011 0050 SL19 - PROFILE 2m	
 27011 0060 SL19 - PROFILE 3m	

Notes: