



COMPO L SOFT 93020

9 15736 9020 B



AVAILABLE IN

BLACK 9 15736 9020 B

CHROMED 9 15736 9020 C

DARK CHROMED 9 15736 9020 DC

WHITE 9 15736 9020 W



[View on website](#)



General info	
LOCATION	indoor
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	round - 135
RECESSED DEPTH (MM)	130
THICKNESS OF MOUNTING SURFACE (MM)	max.25
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.462
ADJUSTABILITY	0° to 30° swiveling, 355° rotatable
INFORMATION	Accessories are not applicable with Compo Large Soft Dim 9 15736 9020

Electrical info	
CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	F

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 20,1W / CRI>90 / 3000K-1800K / 2264lm
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	20°
LED TECHNICS (LIGHT SOURCE)	2264lm // 20,1W // 112lm/W
LED TECHNICS (LUMINAIRE)	1302lm // 23,1W // 56lm/W

Requirements	
LED POWER SUPPLY 600 mA - DC	

Accessories	
COMPO L HONEYCOMB SINGLE USE B	
COMPO L LINEAR SPREAD LENS	
COMPO L SPREAD LENS	
COMPO L SOFTENING LENS	
COMPO L GLASS SBL	

For detailed installation instructions, please consult the manual : [9 15736 XXX0 HAND.pdf](#)

DELTALIGHT

COMPO L SOFT 93020

9 15736 9020 B

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit	
	 15710 0030 - MOUNTING KIT COMPO L TRIM	Required
	 15710 0060 - MOUNTING KIT COMPO L TRIMLESS	Required
	 15710 0030 - MOUNTING KIT COMPO L TRIM	Required
	 15710 0060 - MOUNTING KIT COMPO L TRIMLESS	Required
	 15710 0030 - MOUNTING KIT COMPO L TRIM	Required
	 15710 0060 - MOUNTING KIT COMPO L TRIMLESS	Required

FINISH YOUR SPECIFICATION

LED Power supply

of Fixtures



of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current

15710 4300

LED POWER SUPPLY MULTIPOWER 30W DIM8 600mA

1

15710 4800

LED POWER SUPPLY MULTIPOWER 20W DIM1 600mA

1

15710 5500

LED POWER SUPPLY MULTIPOWER 20W DALI DT6 600mA

1

Dimtype: DALI

Mounting kits



15710 0030 B MOUNTING KIT COMPO L TRIM B

Cutout dimension (mm): 92

15710 0030 W MOUNTING KIT COMPO L TRIM W



15710 0060 MOUNTING KIT COMPO L TRIMLESS

Cutout dimension (mm): 92

DELTALIGHT

COMPO L SOFT 93020

9 15736 9020 B

Light altering devices

15710 2100 B	COMPO L HONEYCOMB SINGLE USE B	☐
15710 2110	COMPO L LINEAR SPREAD LENS	☐
Cutout dimension (mm): 42		
15710 2120	COMPO L SPREAD LENS	☐
Cutout dimension (mm): 42		
15710 2130	COMPO L SOFTENING LENS	☐
Cutout dimension (mm): 42		
15710 2140	COMPO L GLASS SBL	☐
Cutout dimension (mm): 42		

Notes: