

SUPERNOVA LINE 65 930 DIM5



REFERENCE

20622 9305 B

AVAILABLE IN

BLACK 20622 9305 B

WHITE 20622 9305 W



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Surface mounted,Ceiling Suspended
INGRESS PROTECTION	IP20
WEIGHT (KG)	6.3
ADJUSTABILITY	non adjustable
INFORMATION	INCL.PC SBL INCL.DIMMABLE LED POWER SUPPLY

Electrical info

ELECTRICAL	220-240V / 0 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	DALI
ENERGY CLASS	D
CERTIFICATES	CB, ENEC, EPD, RCM

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 58,8W / CRI>90 (R9: 50) / 3000K / 8635lm
TM-30 VALUES	Rf: 92 / Rg: 100
SDCM	SDCM3
RISKGROUP	RG1
LM80	L80 > 60000
LED TECHNICS (LIGHT SOURCE)	8635lm // 58,8W // 147lm/W
LED TECHNICS (LUMINAIRE)	6165lm // 67,6W // 91lm/W

Options

SUSPENSION SET 18 DIM1 3m
CABLE BASE R / S + COVERSET R / S
CENTRAL ROD SUSPENSION
SUPERNOVA 65 RECESSED KIT
WIRELESS CONTROL DIM5


For detailed installation instructions, please consult the manual : [20622_XXX5_HAND.pdf](#)

SUPERNOVA LINE 65 930 DIM5

20622 9305 B

FINISH YOUR SPECIFICATION

Current supply



203 99 55 ANO CABLE BASE R ANO

☐

203 99 55 B CABLE BASE R B

☐

203 99 55 W CABLE BASE R W

☐

203 99 56 ANO CABLE BASE S ANO

☐


203 99 56 B CABLE BASE S B

☐

203 99 56 W CABLE BASE S W

☐

Miscellaneous control equipment




300 90 004 ED5 WIRELESS CONTROL DIM5

☐

Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 45

Recessed kits



274 94 0710 SUPERNOVA 65 RECESSED KIT

☐






Cutout dimension (mm): 735

DELTALIGHT

SUPERNOVA LINE 65 930 DIM5

20622 9305 B



Coversets

	<u>204 00 62 ANO</u>	COVERSET R 62 ANO	☐
	<u>204 00 62 B</u>	COVERSET R 62 B	☐
	<u>204 00 62 W</u>	COVERSET R 62 W	☐
	<u>204 00 90 ANO</u>	COVERSET R 90 ANO	☐
	<u>204 00 90 B</u>	COVERSET R 90 B	☐
	<u>204 00 90 W</u>	COVERSET R 90 W	☐
	<u>204 00 100 ANO</u>	COVERSET R 100 ANO	☐
	<u>204 00 100 B</u>	COVERSET R 100 B	☐
	<u>204 00 100 W</u>	COVERSET R 100 W	☐
	<u>204 62 62 ANO</u>	COVERSET S 62 ANO	☐
	<u>204 62 62 B</u>	COVERSET S 62 B	☐
	<u>204 62 62 W</u>	COVERSET S 62 W	☐
	<u>204 80 80 ANO</u>	COVERSET S 80 ANO	☐
	<u>204 80 80 B</u>	COVERSET S 80 B	☐




DELTALIGHT

SUPERNOVA LINE 65 930 DIM5

20622 9305 B

	<u>204 80 80 W</u>	COVERSET S 80 W	☐
	<u>204 90 90 ANO</u>	COVERSET S 90 ANO	☐
	<u>204 90 90 B</u>	COVERSET S 90 B	☐
	<u>204 90 90 W</u>	COVERSET S 90 W	☐

Suspension parts

	<u>328 18 43 ED1</u>	SUSPENSION SET 18 DIM1 3m	☐
	Dimtype: 1-10V		
	<u>328 24 61 B</u>	CENTRAL ROD SUSPENSION 65 1m B	☐
	<u>328 24 61 W</u>	CENTRAL ROD SUSPENSION 65 1m W	☐
	<u>328 24 91 B</u>	CENTRAL ROD SUSPENSION 95 1m B	☐
	<u>328 24 91 W</u>	CENTRAL ROD SUSPENSION 95 1m W	☐

Electric connection parts

	<u>15225 0360 B</u>	CONNECTION ST B	☐
	Cutout dimension (mm): 43		
	<u>15225 0360 W</u>	CONNECTION ST W	☐

DELTALIGHT

SUPERNOVA LINE 65 930 DIM5

20622 9305 B

Notes: