
DELTALIGHT




SUPERNOVA LINE 65 930 DIM5

REFERENCE 20622 9305 B

AVAILABLE IN
BLACK 20622 9305 B
WHITE 20622 9305 W





View on website

General info	
LOCATION	indoor
INSTALLATION	Ceiling Surface mounted,Ceiling Suspended
INGRESS PROTECTION	IP20
WEIGHT (KG)	6.3
ADJUSTABILITY	non adjustable
INFORMATION	INCL.PC SBL INCL.DIMMABLE LED POWER SUPPLY

Electrical info	
ELECTRICAL	220-240V / 0|50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	DALI
ENERGY CLASS	D
CERTIFICATES	CB, ENEC, EPD, RCM

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 58,8W / CRI>90 (R9: 50) / 3000K / 8635lm
TM-30 VALUES	Rf: 92 / Rg: 100
SDCM	SDCM3
RISKGROUP	RG1
LM80	L80 > 60000
LED TECHNICS (LIGHT SOURCE)	8635lm // 58,8W // 147lm/W
LED TECHNICS (LUMINAIRE)	6165lm // 67,6W // 91lm/W

Options

SUSPENSION SET 18 DIM1 3m
CABLE BASE R / S + COVERSET R / S
CENTRAL ROD SUSPENSION
SUPERNOVA 65 RECESSED KIT
WIRELESS CONTROL DIM5

For detailed installation instructions, please consult the manual : **20622_XXX5_HAND.pdf**


DELTALIGHT

SUPERNOVA LINE 65 930 DIM5

20622 9305 B

FINISH YOUR SPECIFICATION

Current supply



203 99 55 ANO CABLE BASE R ANO ☐

203 99 55 B CABLE BASE R B ☐

203 99 55 W CABLE BASE R W ☐




203 99 56 ANO CABLE BASE S ANO ☐

203 99 56 B CABLE BASE S B ☐

203 99 56 W CABLE BASE S W ☐

Miscellaneous control equipment



300 90 004 ED5 WIRELESS CONTROL DIM5 ☐

Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 45

Recessed kits








274 94 0710 SUPERNOVA 65 RECESSED KIT ☐

Cutout dimension (mm): 735

SUPERNOVA LINE 65 930 DIM5

20622 9305 B


Coversets

	**204 00 62 ANO**	COVERSET R 62 ANO
	204 00 62 B	COVERSET R 62 B
	204 00 62 W	COVERSET R 62 W
	**204 00 90 ANO**	COVERSET R 90 ANO
	204 00 90 B	COVERSET R 90 B
	204 00 90 W	COVERSET R 90 W
	**204 00 100 ANO**	COVERSET R 100 ANO
	204 00 100 B	COVERSET R 100 B
	204 00 100 W	COVERSET R 100 W
	**204 62 62 ANO**	COVERSET S 62 ANO
	204 62 62 B	COVERSET S 62 B
	204 62 62 W	COVERSET S 62 W
	**204 80 80 ANO**	COVERSET S 80 ANO
	204 80 80 B	COVERSET S 80 B

SUPERNOVA LINE 65 930 DIM5

20622 9305 B

204 80 80 W COVERSET S 80 W



204 90 90 ANO COVERSET S 90 ANO


204 90 90 B COVERSET S 90 B

204 90 90 W COVERSET S 90 W

Suspension parts


328 18 43 ED1 SUSPENSION SET 18 DIM1 3m

Dimtype: 1-10V



328 24 61 B CENTRAL ROD SUSPENSION 65 1m B


328 24 61 W CENTRAL ROD SUSPENSION 65 1m W



328 24 91 B CENTRAL ROD SUSPENSION 95 1m B

328 24 91 W CENTRAL ROD SUSPENSION 95 1m W

Electric connection parts



15225 0360 B CONNECTION ST B

Cutout dimension (mm): 43

15225 0360 W CONNECTION ST W

SUPERNOVA LINE 65 930 DIM5

20622 9305 B

Notes: