DELTALIGHT

INFORM ST 1104 94067

REFERENCE 25502 9420 W-B

AVAILABLE IN
BLACK-BLACK 25502 9420 B-B
BLACK-FLEMISH GOLD 25502 9420 B-FG
WHITE-BLACK 25502 9420 W-B
WHITE-WHITE 25502 9420 W-W





View on website

General info	
LOCATION	indoor
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	rectangle - 38 x 1117
RECESSED DEPTH (MM)	40
THICKNESS OF MOUNTING SURFACE (MM)	max.12,5
INGRESS PROTECTION	IP20
WEIGHT (KG)	1
ADJUSTABILITY	non adjustable
INFORMATION	48 x REFLECTOR FL-67° EXCL.LED POWER SUPPLY 400/600mA-DC

Electrical info	
CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	E
CERTIFICATES	CB, ENEC

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 14,1-22,3W / CRI>90 (R9: 50) / 4000K / 2227-3221lm
TM-30 VALUES	Rf: 90 / Rg: 101
SDCM	SDCM3
RISKGROUP	RG1
LM80	L80 > 60000
BEAMANGLE	67°
LED TECHNICS (LIGHT SOURCE)	3221lm // 22,3W // 144lm/W
LED TECHNICS (LUMINAIRE)	2812lm // 25,6W // 110lm/W

Requirements

INFORM POWER SUPPLY 25W

For detailed installation instructions, please consult the manual : **25502_XXX0_HAND.pdf**

DELTALIGHT

INFORM ST 1104 94067

25502 9420 W-B

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit
System ceiling	-
Plasterboard	-
Wood	-

FINISH YOUR SPECIFICATION

LED power supplies

of Fixtures

ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current



25510 0395 INFORM POWER SUPPLY 25W DIM5 — 1

Dimtype: DALI



25510 0440 INFORM POWER SUPPLY 25W — 1

Dimtype: non-dimmable

Notes: