



BOXY R HE 93040 DIM8

10749 9338 B-FG

AVAILABLE IN


BLACK-BLACK 10749 9338 B-B

BLACK-FLEMISH BRONZE 10749 9338 B-FBR

BLACK-FLEMISH GOLD 10749 9338 B-FG

WHITE-BLACK 10749 9338 W-B

WHITE-WHITE 10749 9338 W-W



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Surface mounted
INGRESS PROTECTION	IP20
PROTECTION AGAINST MECHANICAL IMPACT	IK03
WEIGHT (KG)	0.6
ADJUSTABILITY	non adjustable
INFORMATION	LENS WFL-40° INCL.DIMMABLE LED POWER SUPPLY 350mA-DC

Electrical info

ELECTRICAL	220-240V / 50-60Hz
CLASS	II
POWER SUPPLY	YES
DIM TYPE	mains (phase cut-off)
ENERGY CLASS	D
CERTIFICATES	LCA

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 6W / CRI>90 (R9: 50) / 3000K / 945lm
TM-30 VALUES	rf: 96 / Rg: 99
SDCM	SDCM2
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	40°
LED TECHNICS (LIGHT SOURCE)	945lm // 6W // 157lm/W
LED TECHNICS (LUMINAIRE)	797lm // 6,9W // 115lm/W

Remarks

High Efficacy : > 100lm/W

For detailed installation instructions, please consult the manual : [10749_XXX8_HAND.pdf](#)

DELTALIGHT

BOXY R HE 93040 DIM8

10749 9338 B-FG

Notes: