



OML50 - INFORM DU HO 656mm 16LED 94063

31432 9430 B

BESCHIKBAAR IN
ZWART 31432 9430 B

 [Bekijk op website](#)



Algemene info

LOCATIE	binnen
STOF EN WATERDICHTHEID	IP20
GEWICHT (KG)	0.7
INFO	CLUSTER DOWN: 5552lm/m CLUSTER UP: 2776lm/m INCL.LED POWER SUPPLY CABLING 1 CIRCUIT

Elektrische info

INGANGSSPANNING	220-240V / 0 50-60Hz
KLASSE	I
VOEDING	YES
DIM TYPE	niet dimbaar
ENERGIE KLASSE	D
CERTIFICATEN	EPD, RCM

Info lichtbron

LIGHTSOURCE NAME	LED
LICHTBRON	DOWN: LED cluster 24,2W / CRI>90 (R9: 50) / 4000K / 3642lm UP: LED cluster 12,1W / CRI>90 (R9: 50) / 4000K / 1821lm
TM-30-15 WAARDEN	Rf: 90 / Rg: 101
SDCM	SDCM3
RISK-GROEP	RG1
LM80	L80 > 60000
BEAMANGLE	63°
LED TECHNIEK (LICHTBRON)	DOWN: 3642lm // 24,2W // 151lm/W UP: 1821lm // 12,1W // 151lm/W

Notes: