DELTALIGHT



BOXY XL R 93037 DIM5

REFERENCE 10722 9335 B-B

AVAILABLE IN
BLACK-BLACK 10722 9335 B-B
WHITE-BLACK 10722 9335 W-B
WHITE-WHITE 10722 9335 W-W





View on website

General info	
LOCATION	indoor
INSTALLATION	Ceiling Surface mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	1.5
ADJUSTABILITY	non adjustable
INFORMATION	REFLECTOR FL-37° INCL.DIMMABLE LED POWER SUPPLY 500mA-DC

Electrical info	
ELECTRICAL	220-240V / 50-60Hz
CLASS	II
POWER SUPPLY	YES
DIM TYPE	DALI
ENERGY CLASS	C
CERTIFICATES	CB, ENEC, LCA, RCM

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 16,3W / CRI>90 (R9: 52) / 3000K / 2309lm
TM-30 VALUES	Rf: 90 / Rg: 99
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	37°
LED TECHNICS (LIGHT SOURCE)	2309lm // 16,3W // 142lm/W
LED TECHNICS (LUMINAIRE)	2058lm // 19W // 110lm/W

Accessories

HONEYCOMB 78
SOFTENING LENS 78
GLASS SBL 78

For detailed installation instructions, please consult the manual : **10722_XXX5_HAND.pdf**

DELTALIGHT

BOXY XL R 93037 DIM5

10722 9335 B-B

FINISH YOUR SPECIFICATION

Light altering devices



201 02 01 B HONEYCOMB 78 B ☐



201 02 04 SOFTENING LENS 78 ☐



201 02 05 GLASS SBL 78 ☐

Notes: