

QOBY



Clean and simple, Qoby is a surface-mounted luminaire available in a square or round shape with an integral driver to simplify installation. The LED engine of the Qoby is installed deeper into the luminaire, reducing the cut-off angle and the impact on the eye and therefore improving the visual comfort.

Specification	
LED Aperture:	1 ⁵ / ₁₆ "
Installation Method:	1/2" EMT or 4" J-Box
Adjustability:	Fixed
Rating:	IP20

Performance	
LED Maintenance:	L70>50,000h
McAdam Step:	2
CRI:	90
*SP:	10.4W

Delivered Lumens	2700K	3000K	3500K
Optic:	33°	33°	33°
QOBY R:	898Lm	936Lm	965Lm
QOBY S:	858Lm	894Lm	922Lm

Listing

ETL certified to US and Canadian safety standards.

Warranty

5-year limited warranty.

Ordering

ALL BOXES MUST BE FILLED IN TO CORRECTLY ORDER

Example: QBYS-SP3330F-B-PXINCD8-120

Luminaire	Shape	Power*	Optic	CCT	Function	Finish	Installation	Application	Controls***
QBY QOBY	R Round S Square	SP Standard Power	33 33°	27 2700K 30 3000K 35 3500K	F Fixed	B Black W White	MK Mud kit into drywall over 4" junction box PX Coverplate for 4" junction box in corresponding finish NA No Accessory, utilizing 1/2" EMT installation	INC Integral Power Supply	D8-120 FE ELV dim 120V

*** Contact factory for additional dimming options.


Related Products

Minigrd On



Finish Options


QOBY R



BLACK

WHITE


QOBY S



BLACK


WHITE

MK - MUD KIT 1




With Shape R

MK - MUD KIT 2




With Shape S

PX - COVERPLATE R 126



With Shape R


PX - COVERPLATE S 141




With Shape S

Photometric Options

QOBY R



QOBY S



Driver Options

D8

- Dimming Control Phase Control
- Dimming Range 10-100%
- Dim to off no
- Power Factor @ Full Load >0.9
- Efficiency @ Full Load ≥83
- THD @ Full Load <20%

Dimmer Compatibility

- Leviton IP1106-1LZ / 6631-2
- Lutron DVELV-303P / MAELV-600

As technology changes, please use information above as guidance. For most recent updated information please contact factory. Specifications subject to change without notice.