



## MINIGRID ON 150 92750 DIM8

100044 9238 W-W


AVAILABLE IN

**BLACK-BLACK** 100044 9238 B-B

**BLACK-WHITE** 100044 9238 B-W

**WHITE-BLACK** 100044 9238 W-B

**WHITE-WHITE** 100044 9238 W-W



[View on website](#)



### General info

|                           |                                                             |
|---------------------------|-------------------------------------------------------------|
| <b>LOCATION</b>           | indoor                                                      |
| <b>INSTALLATION</b>       | Ceiling Surface mounted                                     |
| <b>INGRESS PROTECTION</b> | IP20                                                        |
| <b>WEIGHT (KG)</b>        | 1.1                                                         |
| <b>ADJUSTABILITY</b>      | 0° to 20° swiveling, 350° rotatable                         |
| <b>INFORMATION</b>        | REFLECTOR FL-50°<br>INCL.DIMMABLE LED POWER SUPPLY 500mA-DC |

### Electrical info

|                     |                       |
|---------------------|-----------------------|
| <b>ELECTRICAL</b>   | 220-240V / 50-60Hz    |
| <b>CLASS</b>        | II                    |
| <b>POWER SUPPLY</b> | YES                   |
| <b>DIM TYPE</b>     | mains (phase cut-off) |
| <b>ENERGY CLASS</b> | E                     |

### Lightsource info

|                                    |                                                   |
|------------------------------------|---------------------------------------------------|
| <b>LIGHTSOURCE NAME</b>            | LED                                               |
| <b>LIGHTSOURCE</b>                 | LED array 8,6W / CRI>90 (R9: 60) / 2700K / 1041lm |
| <b>TM-30 VALUES</b>                | rf: 89 / Rg: 100                                  |
| <b>SDCM</b>                        | SDCM1                                             |
| <b>RISKGROUP</b>                   | RG1                                               |
| <b>LM80</b>                        | L90B10 > 50000                                    |
| <b>BEAMANGLE</b>                   | 50°                                               |
| <b>LED TECHNICS (LIGHT SOURCE)</b> | 1041lm // 8,6W // 121lm/W                         |
| <b>LED TECHNICS (LUMINAIRE)</b>    | 838lm // 9,9W // 85lm/W                           |

For detailed installation instructions, please consult the manual : [100044\\_XXX8\\_HAND.pdf](#)

FINISH YOUR SPECIFICATION

Miscellaneous control equipment



**300 90 004 ED8** WIRELESS CONTROL DIM8

Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 40



Notes: