DELTALIGHT®

STIP W R 830 A

223 54 83 A

AVAILABLE IN
ALU GREY 223 54 83 A
ANTHRACITE (DARK GREY) 223 54 83 N





View on website

General info	
LOCATION	outdoor
INSTALLATION	Wall Surface mounted
INGRESS PROTECTION	IP55
WEIGHT (KG)	0.6
ADJUSTABILITY	non adjustable
INFORMATION	INCL.GLASS INCL.LED POWER SUPPLY 350mA-DC

Electrical info	
ELECTRICAL	100-240V / 50-60Hz
CLASS	II
POWER SUPPLY INCLUDED	YES
DIM TYPE	non-dimmable
ENERGY CLASS	F

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 3,9W / CRI>90 (R9: 55) / 3000K / 385lm
TM-30 VALUES	Rf: 92 / Rg: 98
SDCM	SDCM2
RISKGROUP	RG2 (threshold 0,6m)
LM80	L90B10 > 41000
LED TECHNICS (LIGHT SOURCE)	385lm // 3,9W // 98lm/W
LED TECHNICS (LUMINAIRE)	265lm // 4W // 59lm/W

For detailed installation instructions, please consult the manual: **223_54_83_HAND.pdf**

STIP W R 830 A

223 54 83 A

Notes: