





M20/M26H - SPY 66 93018 DIM5

23328 9315 W

AVAILABLE IN  
**BLACK** 23328 9315 B  
**WHITE** 23328 9315 W



 [View on website](#)



General info

|                    |                                                                                             |
|--------------------|---------------------------------------------------------------------------------------------|
| LOCATION           | indoor                                                                                      |
| INSTALLATION       | Low voltage systems Low voltage system mounted                                              |
| INGRESS PROTECTION | IP20                                                                                        |
| WEIGHT (KG)        | 0.6                                                                                         |
| ADJUSTABILITY      | 0° to 90° swiveling, 355° rotatable                                                         |
| INFORMATION        | REFLECTOR SP-18°<br>EXCL.LED POWER SUPPLY 48V-DC<br>Optional REFLECTORS 30° & 45° available |

Electrical info

|              |                    |
|--------------|--------------------|
| ELECTRICAL   | 48V-DC             |
| CLASS        | III                |
| DIM TYPE     | DALI               |
| ENERGY CLASS | E                  |
| CERTIFICATES | CB, ENEC, EPD, LCA |

Lightsource info

|                             |                                                  |
|-----------------------------|--------------------------------------------------|
| LIGHTSOURCE NAME            | LED                                              |
| LIGHTSOURCE                 | LED array 25W / CRI>90 (R9: 52) / 3000K / 2811lm |
| TM-30 VALUES                | rf: 90 / Rg: 99                                  |
| SDCM                        | SDCM1                                            |
| RISKGROUP                   | RG1                                              |
| LM80                        | L90B10 > 50000                                   |
| BEAMANGLE                   | 18°                                              |
| LED TECHNICS (LIGHT SOURCE) | 2811lm // 25W // 112lm/W                         |
| LED TECHNICS (LUMINAIRE)    | 2007lm // 28,8W // 70lm/W                        |

Remarks

Take a look at our [MAGNETIC PROFILES](#) movie

Requirements

SPY 66 TUBE  
LED POWER SUPPLY 48V-DC

Accessories

HONEYCOMB 57

# DELTALIGHT

## M20/M26H - SPY 66 93018 DIM5

23328 9315 W

For detailed installation instructions, please consult the manual : [23328\\_XXX5\\_HAND.pdf](#)


### FINISH YOUR SPECIFICATION

#### LED power supplies

#### # of Fixtures

 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.


Min current | Max current



**300 89 48 100** LED POWER SUPPLY 48V-DC / 100W DIN

3


Dimtype: non-dimmable



**300 89 48 240** LED POWER SUPPLY 48V-DC / 240W DIN

8

Dimtype: non-dimmable




**21012 0230** LED POWER SUPPLY 48V-DC / 100W

3

Dimtype: non-dimmable

Cutout dimension (mm): 40




**21012 0240** LED POWER SUPPLY 48V-DC / 200W

7

Dimtype: non-dimmable

Cutout dimension (mm): 40

#### Light altering devices




**24611 0150 B** HONEYCOMB 57 SINGLE USE B

# DELTALIGHT

## M20/M26H - SPY 66 93018 DIM5

23328 9315 W

### Finish your product



**24611 0100 B** SPY 66 TUBE B

☐

**24611 0100 FBR** SPY 66 TUBE FBR

☐

**24611 0100 FG** SPY 66 TUBE FG

☐

**24611 0100 GC** SPY 66 TUBE GC

☐

**24611 0100 W** SPY 66 TUBE W

☐

### Replaceable reflector / lens



**24611 0220** SPY 66 REFLECTOR 18°

☐

**24611 0230** SPY 66 REFLECTOR 30°

☐

**24611 0240** SPY 66 REFLECTOR 45°

☐

## COMPATIBLE COMPOSABLES

### SHIFTLINE M26H + SBL

### Available Colours





**30411 9205** SHIFTLINE M26H + SBL 2m DIM5



# DELTALIGHT





## M20/M26H - SPY 66 93018 DIM5

23328 9315 W

|                                                                                    |                                                |                                                                                       |
|------------------------------------------------------------------------------------|------------------------------------------------|---------------------------------------------------------------------------------------|
|   | <b>30411 9305</b> SHIFTLINE M26H + SBL 2m DIM5 |    |
|   | <b>30412 9205</b> SHIFTLINE M26H + SBL 3m DIM5 |    |
|   | <b>30412 9305</b> SHIFTLINE M26H + SBL 3m DIM5 |    |
|    | <b>30413 9205</b> SHIFTLINE M26H + SBL 4m DIM5 |    |
|  | <b>30413 9305</b> SHIFTLINE M26H + SBL 4m DIM5 |  |

### SHIFTLINE M26H profile

### Available Colours

|                                                                                     |                                       |                                                                                       |
|-------------------------------------------------------------------------------------|---------------------------------------|---------------------------------------------------------------------------------------|
|  | <b>23359 0000</b> SLM26H - PROFILE    |  |
|  | <b>23359 0010</b> SLM26H - PROFILE 1m |  |
|  | <b>23359 0020</b> SLM26H - PROFILE 2m |  |
|  | <b>23359 0030</b> SLM26H - PROFILE 3m |  |

# DELTALIGHT

## M20/M26H - SPY 66 93018 DIM5

23328 9315 W

SPLITLINE M20 ST profile

Available Colours



**23397 0000** SPM20 ST - PROFILE



**23397 0020** SPM20 ST - PROFILE 2m




**23397 0030** SPM20 ST - PROFILE 3m




SPLITLINE M20 profile


Available Colours




**420 20 10 00** SPM20 - PROFILE 1m



**420 20 20 00** SPM20 - PROFILE 2m



**420 20 30 00** SPM20 - PROFILE 3m



**23301 0000** SPM20 - PROFILE B



Notes: