



## M26L - OCTAV 27 92730 MDL

29013 9220 FBR

AVAILABLE IN



**BLACK** 29013 9220 B

**FLEMISH BRONZE** 29013 9220 FBR

**FLEMISH GOLD** 29013 9220 FG

**GOLD COLOURED** 29013 9220 GC

**WHITE** 29013 9220 W



[View on website](#)



| General info                |                                                                             |
|-----------------------------|-----------------------------------------------------------------------------|
| LOCATION                    | indoor                                                                      |
| INSTALLATION                | Low voltage systems Low voltage system mounted                              |
| INGRESS PROTECTION          | IP20                                                                        |
| WEIGHT (KG)                 | 0.3                                                                         |
| ADJUSTABILITY               | 0° to 85° swiveling, 360° rotatable                                         |
| INFORMATION                 | REFLECTOR FL-30°<br>EXCLLED POWER SUPPLY 48V-DC<br>SPY 27 L TUBE B included |
| Electrical info             |                                                                             |
| ELECTRICAL                  | 48V-DC                                                                      |
| CLASS                       | III                                                                         |
| DIM TYPE                    | MDL = 1-10V or DALI or push button                                          |
| ENERGY CLASS                | E                                                                           |
| CERTIFICATES                | CB, ENEC                                                                    |
| Lightsource info            |                                                                             |
| LIGHTSOURCE NAME            | LED                                                                         |
| LIGHTSOURCE                 | LED array 5,8W / CRI>90 (R9: 60) / 2700K / 753lm                            |
| TM-30 VALUES                | rf: 89 / Rg: 100                                                            |
| SDCM                        | SDCM1                                                                       |
| RISKGROUP                   | RG1                                                                         |
| LM80                        | L90B10 > 50000                                                              |
| BEAMANGLE                   | 30°                                                                         |
| LED TECHNICS (LIGHT SOURCE) | 753lm // 5,8W // 129lm/W                                                    |
| LED TECHNICS (LUMINAIRE)    | 276lm // 6,7W // 41lm/W                                                     |

### Remarks

Take a look at our **MAGNETIC PROFILES** movie

### Requirements

LED POWER SUPPLY 48V-DC

### Options

DIMMABLE MODULATOR

For detailed installation instructions, please consult the manual : [29013\\_XXX0\\_HAND.pdf](#)

FINISH YOUR SPECIFICATION

| Current supply                                                                                                                                                                                                                                                                                                             |    | # of Fixtures             |    |             |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----|---------------------------|----|-------------|
|                                                                                                                                                                                                                                                                                                                            |    | Min current   Max current |    |             |
| <div><div><div><div></div><div></div></div><div># of fixtures indicates how many devices can be connected (min -&gt; max) to the power supply. The values before and after the ' ' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.</div></div></div> |    |                           |    |             |
| <div><div><div><div><div></div><div></div></div><div>16</div><div>39</div><div>190</div></div></div><div><div>21032 0030</div><div>SMART 48 MODULATOR PLUG-IN WD</div></div><div><div>Dimtype: WDL = wireless dimmable</div></div></div>                                                                                   | 28 | <div></div>               |    |             |
| <div><div><div><div></div><div></div></div><div># of fixtures indicates how many devices can be connected (min -&gt; max) to the power supply. The values before and after the ' ' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.</div></div></div> |    |                           |    |             |
| <div><div><div><div><div></div><div></div></div><div>93</div><div>56</div><div>78</div></div></div><div><div>300 90 011</div><div>SMART 48 MODULATOR DIM9</div></div><div><div>Dimtype: 1-10V or DALI or push button</div></div></div>                                                                                     |    |                           | 28 | <div></div> |
| <div><div><div><div><div></div><div></div></div><div>93</div><div>56</div><div>78</div></div></div><div><div>300 90 012</div><div>SMART 48 MODULATOR WD</div></div><div><div>Dimtype: WDL = wireless dimmable</div></div></div>                                                                                            |    |                           | 28 | <div></div> |
| <div><div><div><div></div><div></div></div><div># of fixtures indicates how many devices can be connected (min -&gt; max) to the power supply. The values before and after the ' ' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.</div></div></div> |    |                           |    |             |
| <div><div><div><div><div></div><div></div></div><div>55</div><div>100</div><div>90</div></div></div><div><div>300 89 48 100</div><div>LED POWER SUPPLY 48V-DC / 100W DIN</div></div><div><div>Dimtype: non-dimmable</div></div></div>                                                                                      |    |                           | 15 | <div></div> |

# DELTALIGHT

## M26L - OCTAV 27 92730 MDL

29013 9220 FBR

|                                                                                  |                                                         |    |                          |
|----------------------------------------------------------------------------------|---------------------------------------------------------|----|--------------------------|
|  | <b>300 89 48 240</b> LED POWER SUPPLY 48V-DC / 240W DIN | 36 | <input type="checkbox"/> |
| Dimtype: non-dimmable                                                            |                                                         |    |                          |
|  | <b>21012 0230</b> LED POWER SUPPLY 48V-DC / 100W        | 15 | <input type="checkbox"/> |
| Dimtype: non-dimmable                                                            |                                                         |    |                          |
| Cutout dimension (mm): 40                                                        |                                                         |    |                          |
|  | <b>21012 0240</b> LED POWER SUPPLY 48V-DC / 200W        | 30 | <input type="checkbox"/> |
| Dimtype: non-dimmable                                                            |                                                         |    |                          |
| Cutout dimension (mm): 40                                                        |                                                         |    |                          |

### COMPATIBLE COMPOSABLES

| SHIFTLINE M26L profile (+ SHIFTLINE M26L MATRIX)                                                                          | Available Colours                                                                     |
|---------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|
|  <b>23358 0000</b> SLM26L - PROFILE    |  |
|  <b>23358 0010</b> SLM26L - PROFILE 1m |  |
|  <b>23358 0020</b> SLM26L - PROFILE 2m |  |
|  <b>23358 0030</b> SLM26L - PROFILE 3m |  |

Notes: