
DELTALIGHT




PARTOU AC 92733 DIM8

REFERENCE 25217 9228 B

AVAILABLE IN
BLACK 25217 9228 B
FLEMISH BRONZE 25217 9228 FBR
FLEMISH GOLD 25217 9228 FG
WHITE 25217 9228 W





View on website

General info	
LOCATION	indoor
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	round - 76
RECESSED DEPTH (MM)	90
THICKNESS OF MOUNTING SURFACE (MM)	min.5
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.3
ADJUSTABILITY	non adjustable
INFORMATION	REFLECTOR FL-33°

Electrical info	
ELECTRICAL	230V / 50-60Hz
CLASS	I
DIM TYPE	mains (phase cut-off)
ENERGY CLASS	G

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	AC LED array 8W / CRI>90 (R9: 55) / 2700K / 597lm
TM-30 VALUES	Rf: 92 / Rg: 98
SDCM	SDCM3
RISKGROUP	RG1
LM80	L80B10 > 67000
BEAMANGLE	33°
LED TECHNICS (LIGHT SOURCE)	597lm // 8W // 75lm/W
LED TECHNICS (LUMINAIRE)	504lm // 8W // 63lm/W

Options

PLASTERKIT 101

For detailed installation instructions, please consult the manual : **25217_XXX8_HAND.pdf**

DELTALIGHT

PARTOU AC 92733 DIM8


25217 9228 B

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit	
 **System ceiling**	-	
 **Plasterboard**	-	
 **Stucanet**	202 11 19 - PLASTERKIT 101	Required
 **Wood**	-	
 **Concrete + plaster**	202 11 19 - PLASTERKIT 101	Required
 **Lintel + plaster**	202 11 19 - PLASTERKIT 101	Required
 **Hollow-core slab + plaster**	202 11 19 - PLASTERKIT 101	Required
 **Stretched ceiling**	-	

FINISH YOUR SPECIFICATION

Plasterkits



202 11 19 PLASTERKIT 101

Cutout dimension (mm): 80 x 180

Notes: