





SPL14 - SPY 20 92730 DIM5

27312 9225 FBR

AVAILABLE IN
BLACK 27312 9225 B
FLEMISH BRONZE 27312 9225 FBR
FLEMISH GOLD 27312 9225 FG
GOLD COLOURED 27312 9225 GC
WHITE 27312 9225 W



[View on website](#)



General info	
LOCATION	indoor
INSTALLATION	Low voltage systems Low voltage system mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.1
ADJUSTABILITY	0° to 90° swiveling, 355° rotatable
INFORMATION	REFLECTOR FL-30° EXCLLED POWER SUPPLY 48V-DC SPY 20 TUBE B included
Electrical info	
ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	DALI
ENERGY CLASS	E
CERTIFICATES	CB, ENEC
Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 2W / CRI>90 (R9: 55) / 2700K / 220lm
TM-30 VALUES	rf: 91 / Rg: 100
SDCM	SDCM3
RISKGROUP	RG2
LM80	L90B10 > 150000
BEAMANGLE	30°
LED TECHNICS (LIGHT SOURCE)	220lm // 2W // 110lm/W
LED TECHNICS (LUMINAIRE)	166lm // 2,3W // 72lm/W

Requirements

LED POWER SUPPLY 48V-DC

For detailed installation instructions, please consult the manual : [27312_XXX5_HAND.pdf](#)

SPL14 - SPY 20 92730 DIM5

27312 9225 FBR

FINISH YOUR SPECIFICATION

LED power supplies

of Fixtures



of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current



300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN

37

Dimtype: non-dimmable



300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN

90

Dimtype: non-dimmable



21012 0230 LED POWER SUPPLY 48V-DC / 100W

37

Dimtype: non-dimmable

Cutout dimension (mm): 40



21012 0240 LED POWER SUPPLY 48V-DC / 200W

75

Dimtype: non-dimmable

Cutout dimension (mm): 40

COMPATIBLE COMPOSABLES

D-LINER SHIFTLINE 19

Available Colours



29110 0010 D-LINER 19 SL PROFILE SET SAPP 2m




29110 0030 D-LINER 19 SL PROFILE SET 30BD 2m



SPLITLINE 14 profile

Available Colours




27300 0020 SPL14 - PROFILE 2m



DELTALIGHT

SPL14 - SPY 20 92730 DIM5

27312 9225 FBR



27300 0030 SPL14 - PROFILE 3m



Notes: