



## SOLI - 52 92720 MDL

27112 9220 GC

AVAILABLE IN  
**BLACK** 27112 9220 B  
**GOLD COLOURED** 27112 9220 GC  
**WHITE** 27112 9220 W



 [View on website](#)



### General info

<b>LOCATION</b>	indoor
<b>INSTALLATION</b>	Low voltage systems Low voltage system mounted
<b>INGRESS PROTECTION</b>	IP20
<b>WEIGHT (KG)</b>	0.4
<b>ADJUSTABILITY</b>	0° to 90° swiveling, 360° rotatable
<b>INFORMATION</b>	REFLECTOR FL-20° EXCL.LED POWER SUPPLY 48V-DC Optional REFLECTORS 30° & 45° available

### Electrical info

<b>ELECTRICAL</b>	48V-DC
<b>CLASS</b>	III
<b>DIM TYPE</b>	MDL = 1-10V or DALI or push button
<b>ENERGY CLASS</b>	E
<b>CERTIFICATES</b>	CB, ENEC, LCA

### Lightsource info

<b>LIGHTSOURCE NAME</b>	LED
<b>LIGHTSOURCE</b>	LED array 10,3W / CRI>90 (R9: 60) / 2700K / 1224lm
<b>TM-30 VALUES</b>	rf: 89 / Rg: 100
<b>SDCM</b>	SDCM1
<b>RISKGROUP</b>	RG1
<b>LM80</b>	L90B10 > 50000
<b>BEAMANGLE</b>	20°
<b>LED TECHNICS (LIGHT SOURCE)</b>	1224lm // 10,3W // 119lm/W
<b>LED TECHNICS (LUMINAIRE)</b>	767lm // 11,8W // 65lm/W

### Requirements

SPY 52 TUBE  
 LED POWER SUPPLY 48V-DC

### Options

DIMMABLE MODULATOR

### Accessories

HONEYCOMB 42  
 SPREAD LENS 42  
 LINEAR SPREAD LENS 42  
 SOFTENING LENS 42  
 GLASS SBL 42

# DELTALIGHT

## SOLI - 52 92720 MDL


27112 9220 GC

For detailed installation instructions, please consult the manual : [27112\\_XXX0\\_HAND.pdf](#)


### FINISH YOUR SPECIFICATION

#### SMART 48

#### # of Fixtures

 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current



**300 90 011** SMART 48 MODULATOR DIM9

16

Dimtype: 1-10V or DALI or push button




**300 90 012** SMART 48 MODULATOR WD

16

Dimtype: WDL = wireless dimmable

#### LED power supplies

#### # of Fixtures

 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current



**300 89 48 100** LED POWER SUPPLY 48V-DC / 100W DIN

8


Dimtype: non-dimmable



**300 89 48 240** LED POWER SUPPLY 48V-DC / 240W DIN

20

Dimtype: non-dimmable



**21012 0230** LED POWER SUPPLY 48V-DC / 100W

8


Dimtype: non-dimmable

Cutout dimension (mm): 40

# DELTALIGHT

## SOLI - 52 92720 MDL

27112 9220 GC



**21012 0240** LED POWER SUPPLY 48V-DC / 200W

16

Dimtype: non-dimmable

Cutout dimension (mm): 40

### Light altering devices



**19810 0010 B** HONEYCOMB 42 SINGLE USE B



**19810 0020** LINEAR SPREAD LENS 42



**19810 0030** SPREAD LENS 42



**19810 0040** SOFTENING LENS 42



**19810 0050** GLASS SBL 42



**19810 0060 B** HONEYCOMB 42 DOUBLE USE B

### Finish your product



**19810 0100 B** SPY 52 TUBE B

**19810 0100 FBR** SPY 52 TUBE FBR

# DELTALIGHT

## SOLI - 52 92720 MDL

27112 9220 GC

**19810 0100 FG** SPY 52 TUBE FG

**19810 0100 GC** SPY 52 TUBE GC

**19810 0100 W** SPY 52 TUBE W

### Replaceable reflector / lens



**19810 0180** SPY 52 REFLECTOR 20°



**19810 0190** SPY 52 REFLECTOR 45°




**19810 0240** SPY 52 REFLECTOR 30°


## COMPATIBLE COMPOSABLES

### SOLISCAPE profile

### Available Colours



**27111 0020** SOLI - PROFILE 2m



**27111 0030** SOLI - PROFILE 3m



Notes: