



OML50 - INFORM DU HO 656mm 16LED 94063 DIM5

31432 9435 B

AVAILABLE IN
BLACK 31432 9435 B

 [View on website](#)



General info

LOCATION	indoor
INGRESS PROTECTION	IP20
WEIGHT (KG)	1
INFORMATION	CLUSTER DOWN: 5552lm/m CLUSTER UP: 2776lm/m INCL.DIMMABLE LED POWER SUPPLY (DALI-2 standard) CABLING 1 CIRCUIT

Electrical info

ELECTRICAL	220-240V / 0 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	DALI
ENERGY CLASS	D
CERTIFICATES	EPD, RCM

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	DOWN: LED cluster 24,2W / CRI>90 (R9: 50) / 4000K / 3642lm UP: LED cluster 12,1W / CRI>90 (R9: 50) / 4000K / 1821lm
TM-30 VALUES	Rf: 90 / Rg: 101
SDCM	SDCM3
RISKGROUP	RG1
LM80	L80 > 60000
BEAMANGLE	63°
LED TECHNICS (LIGHT SOURCE)	DOWN: 3642lm // 24,2W // 151lm/W UP: 1821lm // 12,1W // 151lm/W

Options

WIRELESS CONTROL DIM5

Notes: