DELTALIGHT



OML50 - PRISMATIC LENS D HO 1968mm 940 DIM5

REFERENCE 31615 9405 B

AVAILABLE IN
BLACK 31615 9405 B

View on website

General info	
LOCATION	indoor
INGRESS PROTECTION	IP20
WEIGHT (KG)	2.4
INFORMATION	INCL.DIMMABLE LED POWER SUPPLY (DALI-2 standard) CABLING 1 CIRCUIT

Electrical info	
ELECTRICAL	220-240V / 0|50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	DALI
ENERGY CLASS	D
CERTIFICATES	EPD, RCM

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 46,5W / CRI>90 (R9: 50) / 4000K / 7274lm
TM-30 VALUES	Rf: 90 / Rg: 101
SDCM	SDCM3
RISKGROUP	RG1
LM80	L80 > 60000
LED TECHNICS (LIGHT SOURCE)	7274lm // 46,5W // 160lm/W

Options

WIRELESS CONTROL DIM5

Notes:

Delta Light NV may revise the information and technical data at any time without notice. Version: 08/10/2026