




SPY 66 93018 ADM SLIM DIM5

24626 9315 B

AVAILABLE IN
BLACK 24626 9315 B
WHITE 24626 9315 W



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Mains voltage track Mains voltage track mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.6
ADJUSTABILITY	0° to 90° swiveling, 360° rotatable
INFORMATION	REFLECTOR SP-18° 3F MULTI DIMMABLE POWER SLIM ADAPTER 350-700mA Current selection via jumper on adapter Optional REFLECTORS 30° & 45° available

Electrical info

ELECTRICAL	220-240V / 50-60Hz
CLASS	II
POWER SUPPLY	YES
DIM TYPE	DALI
ENERGY CLASS	E
CERTIFICATES	CB, RCM

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 25W / CRI>90 (R9: 52) / 3000K / 281lm
TM-30 VALUES	rf: 90 / Rg: 99
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	18°
LED TECHNICS (LIGHT SOURCE)	281lm // 25W // 112lm/W
LED TECHNICS (LUMINAIRE)	2007lm // 28,8W // 70lm/W

Requirements

SPY 66 TUBE
 TRACK 3F DIM


Accessories

HONEYCOMB 57

For detailed installation instructions, please consult the manual : [24626_XXX5_HAND.pdf](#)

FINISH YOUR SPECIFICATION


Light altering devices



24611 0150 B HONEYCOMB 57 SINGLE USE B

☐

Finish your product



24611 0100 B SPY 66 TUBE B

☐

24611 0100 FBR SPY 66 TUBE FBR

☐

24611 0100 FG SPY 66 TUBE FG

☐

24611 0100 GC SPY 66 TUBE GC

☐

24611 0100 W SPY 66 TUBE W

☐

Replaceable reflector / lens



24611 0220 SPY 66 REFLECTOR 18°

☐

24611 0230 SPY 66 REFLECTOR 30°

☐

24611 0240 SPY 66 REFLECTOR 45°

☐

SPY 66 93018 ADM SLIM DIM5

24626 9315 B

COMPATIBLE TRACKS

TRACK 3F DIM H			Available Colours
<u>200 14 410</u>	TRACK 3F DIM H 1m	1000 m 1.6 kg	 
<u>200 14 420</u>	TRACK 3F DIM H 2m	2000 m 3.2 kg	 
<u>200 14 430</u>	TRACK 3F DIM H 3m	3000 m 4.8 kg	 
TRACK 3F DIM IN			Available Colours
<u>200 13 410</u>	TRACK 3F DIM IN 1m	1000 m 1.2 kg	 
<u>200 13 420</u>	TRACK 3F DIM IN 2m	2000 m 2.4 kg	 
<u>200 13 430</u>	TRACK 3F DIM IN 3m	3000 m 3.5 kg	 
TRACK 3F DIM ON			Available Colours
<u>200 12 410</u>	TRACK 3F DIM ON 1m	1000 m 1.1 kg	  
<u>200 12 420</u>	TRACK 3F DIM ON 2m	2000 m 2.1 kg	  
<u>200 12 430</u>	TRACK 3F DIM ON 3m	3000 m 3.1 kg	  

Notes: