





SPY 66 93018 ADM SLIM DIM5

24626 9315 B

BESCHIKBAAR IN
ZWART 24626 9315 B
WIT 24626 9315 W



[Bekijk op website](#)



Algemene info

LOCATIE	binnen
INSTALLATIE	Rail systemen Rail montage
STOF EN WATERDICHTHEID	IP20
GEWICHT (KG)	0.6
RICHTBAARHEID	0° tot 90° zwenkbaar, 360° roteerbaar
INFO	REFLECTOR SP-18° 3F MULTI DIMMABLE POWER SLIM ADAPTER 350-700mA Current selection via jumper on adapter Optional REFLECTORS 30° & 45° available

Elektrische info

INGANGSSPANNING	220-240V / 50-60Hz
KLASSE	II
VOEDING	YES
DIM TYPE	DALI
ENERGIE KLASSE	E
CERTIFICATEN	CB, RCM

Info lichtbron

LIGHTSOURCE NAME	LED
LICHTBRON	LED array 25W / CRI>90 (R9: 52) / 3000K / 281lm
TM-30-15 WAARDEN	rf: 90 / Rg: 99
SDCM	SDCM1
RISK-GROEP	RG1
LM80	L90B10 > 50000
BEAMANGLE	18°
LED TECHNIEK (LICHTBRON)	281lm // 25W // 112lm/W
LED TECHNIEK (TOESTEL)	2007lm // 28,8W // 70lm/W

Benodigdheden

SPY 66 TUBE
TRACK 3F DIM

Accessoires

HONEYCOMB 57

Voor gedetailleerde montage gegevens, consulteer de handleiding : [24626_XXX5_HAND.pdf](#)

VERVOLLEDIG UW SPECIFICATIE


Licht veranderende onderdelen



24611 0150 B HONEYCOMB 57 SINGLE USE B

☐

Maak je product af



24611 0100 B SPY 66 TUBE B

☐

24611 0100 FBR SPY 66 TUBE FBR

☐

24611 0100 FG SPY 66 TUBE FG

☐

24611 0100 GC SPY 66 TUBE GC

☐

24611 0100 W SPY 66 TUBE W

☐

Vervangbare reflector / lens



24611 0220 SPY 66 REFLECTOR 18°

☐

24611 0230 SPY 66 REFLECTOR 30°

☐

24611 0240 SPY 66 REFLECTOR 45°

☐

COMPATIBELE TRACKS

TRACK 3F DIM H				Beschikbare kleuren
<u>200 14 410</u>	TRACK 3F DIM H 1m	1000 m	1.6 kg	 
<u>200 14 420</u>	TRACK 3F DIM H 2m	2000 m	3.2 kg	 
<u>200 14 430</u>	TRACK 3F DIM H 3m	3000 m	4.8 kg	 
TRACK 3F DIM IN				Beschikbare kleuren
<u>200 13 410</u>	TRACK 3F DIM IN 1m	1000 m	1.2 kg	 
<u>200 13 420</u>	TRACK 3F DIM IN 2m	2000 m	2.4 kg	 
<u>200 13 430</u>	TRACK 3F DIM IN 3m	3000 m	3.5 kg	 
TRACK 3F DIM ON				Beschikbare kleuren
<u>200 12 410</u>	TRACK 3F DIM ON 1m	1000 m	1.1 kg	  
<u>200 12 420</u>	TRACK 3F DIM ON 2m	2000 m	2.1 kg	  
<u>200 12 430</u>	TRACK 3F DIM ON 3m	3000 m	3.1 kg	  

Notes: