
DELTALIGHT




Image may differ from the actual product

LEDFLEX IN RGB/TW 5m

REFERENCE 21030 0420





View on website

General info	
LOCATION	indoor
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.1
INFORMATION	MAX.L / FLEX : 5m 96 x SMD LED/m DIVIDABLE PER 62,5mm 24V-DC INCL.10 MOUNTING BRACKETS RGB: 11,52W/m - TW:3,4W/m

Electrical info	
CLASS	III
ENERGY CLASS	G
CERTIFICATES	CB, ENEC

Lightsource info	
LIGHTSOURCE	@ 2700K: 3,4W/m / CRI>90 / 2700K-6000K / 269lm/m Or @ 6000K: 3,4W/m / CRI>90 / 2700K-6000K / 324lm/m Or @ RGB: 11,52W/m

Requirements

LED POWER SUPPLY 24V-DC

For detailed installation instructions, please consult the manual : **21030_0420_HAND.pdf**

WHERE USED

372 01 00	SPT PRO - PROFILE
398 01 00	SHL 20 ST - PROFILE 3m
398 02 00	SHL 18 - PROFILE 3m
398 03 00	SHL 19 - PROFILE 3m

LEDFLEX IN RGB/TW 5m

21030 0420

Notes: