




Image may differ from the actual product

LEDFLEX IN RGB/TW 5m
21030 0420



 [Auf der Website anzeigen](#)



Allgemeine Information	
ANWENDUNGSBEREICH	innenbereich
SCHUTZ GEGEN EINDRINGEN	IP20
GEWICHT (KG)	0.1
INFORMATION	MAX.L / FLEX : 5m 96 x SMD LED/m DIVIDABLE PER 62,5mm 24V-DC INCL.10 MOUNTING BRACKETS RGB: 11,52W/m - TW:3,4W/m
Elektrische Informationen	
KLASSE	III
ENERGIEKLASSE	G
ZERTIFIKATE	CB, ENEC
Lichtquelle Info	
LICHTQUELLE	@ 2700K: 3,4W/m / CRI>90 / 2700K-6000K / 269lm/m Or @ 6000K: 3,4W/m / CRI>90 / 2700K-6000K / 324lm/m Or @ RGB: 11,52W/m
Erforderliches Zubehör	
LED POWER SUPPLY 24V-DC	

Detaillierte Installationsanweisungen finden Sie in der Montageanleitung : [21030_0420_HAND.pdf](#)

WO VERWENDET

- 372 01 00 SPT PRO - PROFILE
- 398 01 00 SHL 20 ST - PROFILE 3m
- 398 02 00 SHL 18 - PROFILE 3m
- 398 03 00 SHL 19 - PROFILE 3m

DELTALIGHT

LED FLEX IN RGB/TW 5m

21030 0420

Notes: