





LEDFLEX IN RGB/TW 5m

21030 0420



[Bekijk op website](#)



Algemene info	
LOCATIE	binnen
STOF EN WATERDICHTHEID	IP20
GEWICHT (KG)	0.1
INFO	MAX.L / FLEX : 5m 96 x SMD LED/m DIVIDABLE PER 62,5mm 24V-DC INCL.10 MOUNTING BRACKETS RGB: 11,52W/m - TW:3,4W/m
Elektrische info	
KLASSE	III
ENERGIE KLASSE	G
CERTIFICATES	CB, ENEC
Info lichtbron	
LICHTBRON	@ 2700K: 3,4W/m / CRI>90 / 2700K-6000K / 269lm/m Or @ 6000K: 3,4W/m / CRI>90 / 2700K-6000K / 324lm/m Or @ RGB: 11,52W/m
Benodigheden	
LED POWER SUPPLY 24V-DC	

Voor gedetailleerde montage gegevens, consulteer de handleiding : [21030_0420_HAND.pdf](#)

WAAR GEBRUIKT

- 372 01 00** SPT PRO - PROFILE
- 398 01 00** SHL 20 ST - PROFILE 3m
- 398 02 00** SHL 18 - PROFILE 3m
- 398 03 00** SHL 19 - PROFILE 3m

DELTALIGHT

LED FLEX IN RGB/TW 5m

21030 0420

Notes: