



COMPO L SOFT 93050

9 15736 9040 B



AVAILABLE IN

NOIR 9 15736 9040 B

CHROME 9 15736 9040 C

CHROME FONCÉ 9 15736 9040 DC

BLANC 9 15736 9040 W



[View on website](#)



General info

LOCATION	interieur
INSTALLATION	Plafond Encastré
CUTOUT SHAPE/SIZE (MM)	circulaire - 135
RECESSED DEPTH (MM)	130
THICKNESS OF MOUNTING SURFACE (MM)	max.25
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.462
ADJUSTABILITY	0° à 30° inclinable, 355° rotatif

Electrical info

CLASS	III
DIM TYPE	selon le type d'alimentation externe
ENERGY CLASS	F

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 20,1W / CRI>90 / 3000K-1800K / 2264lm
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	50°
LED TECHNICS (LIGHT SOURCE)	2264lm // 20,1W // 112lm/W
LED TECHNICS (LUMINAIRE)	1474lm // 23,1W // 64lm/W

Requirements

LED POWER SUPPLY 600 mA - DC

Accessories

COMPO L HONEYCOMB SINGLE USE B
COMPO L LINEAR SPREAD LENS
COMPO L SPREAD LENS
COMPO L SOFTENING LENS
COMPO L GLASS SBL


For detailed installation instructions, please consult the manual : [9_15736_XXX0_HAND.pdf](#)

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit	
	 15710 0030 - MOUNTING KIT COMPO L TRIM	Required
	 15710 0060 - MOUNTING KIT COMPO L TRIMLESS	Required
	 15710 0030 - MOUNTING KIT COMPO L TRIM	Required
	 15710 0060 - MOUNTING KIT COMPO L TRIMLESS	Required
	 15710 0030 - MOUNTING KIT COMPO L TRIM	Required
	 15710 0060 - MOUNTING KIT COMPO L TRIMLESS	Required

FINISH YOUR SPECIFICATION

alimentation led		# of Fixtures
 web2print_power_supply_info_box		Min current Max current
15710 4300	LED POWER SUPPLY MULTIPOWER 30W DIM8 600mA	1 ☐
15710 4800	LED POWER SUPPLY MULTIPOWER 20W DIM1 600mA	1 ☐
15710 5500	LED POWER SUPPLY MULTIPOWER 20W DALI DT6 600mA	1 ☐
Dimtype: DALI		

kit de montage	
	15710 0030 B MOUNTING KIT COMPO L TRIM B ☐
Cutout dimension (mm): 92	
	15710 0030 W MOUNTING KIT COMPO L TRIM W ☐
	15710 0060 MOUNTING KIT COMPO L TRIMLESS ☐
Cutout dimension (mm): 92	

DELTALIGHT

COMPO L SOFT 93050

9 15736 9040 B

modifier les dispositifs de lumière

15710 2100 B

COMPO L HONEYCOMB SINGLE USE B

☐

15710 2110

COMPO L LINEAR SPREAD LENS

☐

Cutout dimension (mm): 42

15710 2120

COMPO L SPREAD LENS

☐

Cutout dimension (mm): 42

15710 2130

COMPO L SOFTENING LENS

☐

Cutout dimension (mm): 42

15710 2140

COMPO L GLASS SBL

☐

Cutout dimension (mm): 42

Notes: